

	SWITCH POE DS-3E0526P-E 24-PORT SFP Hikvision	SPEAKER CABLE HI- EI/2X0.5	UPS AT-UPS1500S-RT-RACK 1500 VA EAST	DC FILTER FDC-08 TO SWITCHING ADAPTERS
				
	175192.31 HUF 175192.31 HUF	125.00 HUF 125.00 HUF	123045.19 HUF 123045.19 HUF	3843.27 HUF 3843.27 HUF
Power adapter type	Line-interactive	...
Maximal current	0.8 A
Nominal power	1200 W	...
Apparent Power	1500 VA	...
Power connectors type	2.1/5/5 mm plug
In section	...	100 m . Price for 1m when buying a whole roll
Input voltage	230 V AC \pm 25 %	...
Input frequency	50 / 60 Hz (auto detection)	...
Inner conductor	...	2 x \varnothing 0.5 mm Cu-OFC Stranded wire
Output voltage	230 V AC \pm 10 % (Pure Sine Wave)	...
Outer coating	...	PVC
Coating color	...	Colorless
Output frequency	50 / 60 Hz \pm 1 %	...
Voltage adjustment	—	...
LAN ports	<ul style="list-style-type: none"> • 24 x RJ45 10/100/1000 Base-TX (24 x PoE (802.3af/at)), • 1 x RJ45 10/100/1000 Base-TX - Uplink, • 1 x port SFP 10/100/1000 Base-TX - Uplink
Frequency adjustment	—	...
Transfer time	\leq 10 ms	...
Charging time (recover to 90% capacity)	8 hours	...
Battery	2 x 12V/9Ah	...
Transmission speed	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps - 24 LAN & PoE ports, • 10 / 100 / 1000 Mbps - 2 Uplink ports
Maximal output power	30 W / port PoE
Maximal total power	370 W
MAC addresses table	8k
Management	—
LED diodes	Power, Link/Act, PoE, PoE Max
Certificates	CE, FCC, RoHS
Power supply	100 ... 240 V AC
Housing	Metal
Operation temp	-10 °C ... 55 °C

Estimated battery operation time	<ul style="list-style-type: none"> • 41 minutes @ 100 W, • 22 minutes @ 200 W, • 15 minutes @ 300 W, • 9 minutes @ 400 W, • 6.5 minutes @ 500 W, • 4 minutes @ 600 W, • 2 minutes @ 700 W, • 2 minutes @ 800 W, • 1.5 minutes @ 900 W, • 42 s @ 1000 W 	...
SAP Code	301801380
Number of outputs	6 pcs - 3 x CEE 7/3 (Schuko), 3 x IEC C13	...
Management software	UPSmart (Windows 95/98/2000/XP/Vista/7/8/10, Linux)	...
Protections	<ul style="list-style-type: none"> • Fuse • Short-circuit • Overload • Overvoltage - RJ45 • Ethernet filter • Output voltage filtering • DC filter to eliminate interferences - EMI/RFI 	...
Operation state indication	<ul style="list-style-type: none"> • LCD display: operation mode, battery charging level, in/out voltage level, overload indicator, LED diodes, • Sound signaling 	...
Main features	<ul style="list-style-type: none"> • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Overvoltage protection : 6 kV - PoE ports • Can be mounted in a Rack 19" cabinet 	...	<ul style="list-style-type: none"> • Auto restart while AC is recovering • Excellent microprocessor control guarantees high reliability • COLD START function for manual switch to the battery power supply • Automatic Voltage Regulator (AVR) • Battery charge and maintenance control • 2 x RJ45 - Input / Output • Port USB 2.0 - Access from PC • Remote management - UPSmart application (included) • Optical - sound signaling • Built-in EMI, RFI filter • Network card slot • Can be mounted in a Rack 19" cabinet • The device works with power supply adapters having Active Power Factor Correction (APFC) 	...



Application	<ul style="list-style-type: none"> • Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment 	...
Housing type	Rack/Tower 2-in-1 Design	2.1/5.5 mm socket
Operation temp. / Relative humidity	5 °C ... 40 °C / ≤ 93 % (non-condensing)	...
Weight	2.9 kg	...	17.1 kg	0.02 kg
Dimensions	440 x 221 x 44 mm	...	440 x 132 x 410 mm ; RACK 19", 3U	26 x 21 x 16 mm
Manufacturer / Brand	Hikvision	...	EAST	DELTA
Guarantee	3 years	2 years	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00