




|                          | <a href="#">MOUNTING KIT MONT2-RPT-CDN ACO</a>                                    | <a href="#">NETWORK ADAPTER TL-PA4010KIT TP-LINK</a>  | <a href="#">IP CAMERA IPC-G26-0360B Wi-Fi, - 1080p 3.6 mm DAHUA</a>                 |
|--------------------------|---|---|---|
|                          |  |    |  |
|                          | 1638.46 HUF<br>1638.46 HUF  | 17648.08 HUF<br>17648.08 HUF  | 32692.31 HUF<br>32692.31 HUF  |
| LAN ports                | ...   | 1 Port LAN  | ...   |
| Standard                 | ...   | ...   | TCP/IP  |
| Compatibility            | CDN-R2 mounting frames  | ...   | ...   |
| Sensor                   | ...   | ...   | 1/2.7 " Progressive Scan CMOS   |
| Bush                     | —   | ...   | ...   |
| Matrix size              | ...   | ...   | 2.1 Mpx   |
| Modulation               | ...   | OFDM  | ...   |
| Scanning system          | ...   | ...   | Progressive   |
| Protections              | ...   | 128-bit AES encryption  | ...   |
| Resolution               | ...   | ...   | 1920 x 1080 - 1080p   |
| Lens                     | ...   | ...   | 3.6 mm  |
| LED diodes               | ...   | Power supply, Link/Act, Power network   | ...   |
| View angle               | ...   | ...   | 88 °  |
| Transmission speed       | ...   | 500 Mbps  | ...   |
| Range of IR illumination | ...   | ...   | 30 m  |
| S/N ratio                | ...   | ...   | > 50 dB   |
| Range                    | ...   | 300 m - Within a building   | ...   |
| Image compression method | ...   | ...   | H.265   |
| Alarm inputs / outputs   | ...   | ...   | —   |
| Audio                    | ...   | ...   | Microphone built-in   |
| Main stream frame rate   | ...   | ...   | 25 fps @ 1080p  |
| Network interface        | ...   | ...   | 10/100 Base-T (RJ-45), Wi-Fi IEEE 802.11 b/g/n                                      |
| Main features            | Blades made of stainless steel  | <ul style="list-style-type: none"> <li>• Plug &amp; Play</li> <li>• HomePlug AV compliance</li> <li>• Low current consumption</li> <li>• Max. number of supported devices : 6 pcs</li> <li>• Pair button - Encryption activation</li> </ul> | ...   |
| Network protocols        | ...   | ...   | TCP, DHCP   |
| WEB Server               | ...   | ...   | —   |
| Certificates             | ...   | CE, FCC, RoHS   | ...   |
| ONVIF                    | ...   | ...   | —   |
| Operation temp           | ...   | 0 °C ... 40   | ...   |

|                               |         |                 |  |
|-------------------------------|---------|-----------------|--|
| Memory card slot              | ...     | ...             | Micro SD memory cards up to 128GB support (possible local recording)   |
| Main features                 | ...     | ...             | <ul style="list-style-type: none"> <li>• Wi-Fi Module - IEEE 802.11 b/g/n, Operating range in open area : 100 m (open area) ; Antenna - 2x2 MIMO, SMA type connectors</li> <li>• Motion Detection</li> </ul> |
| Power supply                  | ...     | 230 V AC        | 12 V DC / 630 mA   |
| Power consumption             | ...     | < 2 W           | ≤ 7.5 W  |
| Mobile phones support         | ...     | ...             | Access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">IMOU</a></li> <li>• iOS (iPhone): Free application <a href="#">IMOU</a></li> </ul>                    |
| Default admin user / password | ...     | ...             | admin / admin  |
| Default IP address            | ...     | ...             | DHCP   |
| Web browser access ports      | ...     | ...             | —  |
| PC client access ports        | ...     | ...             | —  |
| Mobile client access ports    | ...     | ...             | —  |
| Port ONVIF                    | ...     | ...             | —  |
| RTSP URL                      | ...     | ...             | —  |
| Housing                       | ...     | ...             | Compact - Metal  |
| Color                         | ...     | ...             | White  |
| "Index of Protection"         | ...     | ...             | IP67   |
| Operation temp                | ...     | ...             | -10 °C ... 50 °C   |
| Weight                        | ...     | 0.075 kg        | 0.48 kg  |
| Dimensions                    | ...     | 65 x 52 x 28 mm | 70 x 107 x 176 mm  |
| Supported languages           | ...     | ...             | —  |
| Manufacturer / Brand          | ACO     | TP-LINK         | DAHUA  |
| Guarantee                     | 2 years | 3 years         | 3 years  |