

| | | | |
|-----------------------|---|---|---|
| | SURFACE BOX 1-GANG LE-664798 Niloe LEGRAND | ACCESS POINT RG- RAP1200(P) 2.4 GHz, 5 GHz 400 Mbps + 867 Mbps REYEE | ACCESS POINT 4G LTE +ROUTER CUDY-LT400 2.4 GHz, 5 GHz, 300 Mbps |
| |  |  |  |
| | 108.28 CZK 108.28 CZK | 2750.91 CZK 2750.91 CZK | 1627.99 CZK 1627.99 CZK |
| Application | Niloe product series | ... | ... |
| Number of sections | 1 | ... | ... |
| Material | Self-extinguishing ABS | ... | ... |
| Color | White | ... | ... |
| Frequency range | ... | 2.4 GHz, 5 GHz | <ul style="list-style-type: none"> • Wi-Fi : 2.4 GHz, 5 GHz, • LTE : 2600 MHz, 2100 MHz, 1800 MHz, 900 MHz, 800 MHz |
| Antenna type | ... | 2.4 GHz / 5 GHz : 2 dBi - Integrated | <ul style="list-style-type: none"> • 2 x Omnidirectional antenna Wi-Fi • 2 x Omnidirectional antenna 4G LTE |
| Standards | ... | IEEE 802.11 a/b/g/n/ac | IEEE 802.11 b/g/n |
| Baud rates | ... | 2.4 GHz : max. 400 Mbps + 5 GHz : max. 867 Mbps | <ul style="list-style-type: none"> • Wi-Fi : 300 Mbps • LTE : 150 Mbps / 50 Mbps |
| LED indicators | ... | ... | Power, INTERNET, LAN/WAN, LAN 1, LAN 2, LAN 3, WiFi, 4G |
| SIM socket | ... | ... | 1 x mini SIM |
| DDNS | ... | ... | ✓ |
| DHCP server | ... | ... | ✓ |
| LAN ports | ... | 1 x 10/100/1000 Mbps PoE IN 1 x 10/100/1000 Mbps LAN + PoE OUT 3 x 10/100/1000 Mbps | 1 x 10/100 Mbps - Uplink / LAN 3 x 10/100 Mbps - LAN |
| Firmware update | ... | ... | ✓ |
| Protections | ... | WPA, WPA2 AES, WPA-PSK | DoS attacks protection, SPI network firewall, domain filtering, IP and MAC filtering, IP and MAC binding |
| Mobile phones support | ... | Android: Free application Ruijie Reyee iOS (iPhone): Free application Ruijie Reyee | ... |
| Management interface | ... | Web browser, Ruijie Cloud | Web browser |

| | | | |
|-------------------------------|---|---|--|
| Transmitter power | ... | < 19 dBm @ 2.4 GHz < 18 dBm @ 5 GHz | ... |
| Housing | ... | Plastic | ... |
| Power supply PoE | ... | ✓ | ... |
| Power supply | ... | PoE (802.3af/at) | 12 V DC / 2.5 A (power adapter included) |
| Power consumption | ... | ≤ 8 W (23.4 W (max)) | ... |
| Operation temp | ... | 0 °C ... 40 °C | 0 °C ... 45 °C |
| Permissible relative humidity | ... | 0 % ... 100 % | 5 % ... 95 % (non-condensing) |
| Main features | ... | <ul style="list-style-type: none"> • MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network • Access Point is managed through the web and the cloud (Ruijie Reyee application) • Number of users : 110 (max) • Enable/Disable Wireless Radio • Wireless transmission statistics • Access control • MAC addresses filtering • Wireless isolation between clients • SSID to VLAN mapping • RESET button | <ul style="list-style-type: none"> • Internet access filtering • Static / dynamic routing • Built-in 4-port switch • Wireless transmission statistics • QoS • Rate limit • Access control • Remote management • DMZ • parental control • Guest Network - a separate and secure network for guests |
| Weight | 0.048 kg | 0.23 kg | 0.264 kg |
| Dimensions | 88.5 x 88.5 x 40 mm Inputs : 20 x 15.5 mm, 32 x 12.5 mm, 40 x 20 mm Input for cable Ø 20 mm | 126 x 85 x 47 mm | 229 x 147 x 32 mm |
| Manufacturer / Brand | LEGRAND | RUIJIE / REYEE | CUDY |
| Guarantee | 2 years | 3 years | 2 years |