





	IP CAMERA DH-IPC-HDW1230SP-036 - 1080p 3.6 mm DAHUA	TRIPLE SMART SWITCH SWITCHBOX-T-PRO/BLEBOX Wi-Fi, 230 V AC	AHD MOBILE CAMERA ATE-CAM-AHD925HD - 1080p 2.8 mm AUTONE	SMART LIGHT SWITCH ATLO-WB1/K-TUYA Wi-Fi, Tuya Smart
				
	174.53 AUD 174.53 AUD	107.80 AUD 107.80 AUD	86.45 AUD 86.45 AUD	15.25 AUD 15.25 AUD
Standard	TCP/IP	...	AHD	...
Sensor	1/2.9 " Progressive Scan CMOS	...	1/3 " Sony CMOS IMX323	...
Scanning system	Progressive	...	...	...
Rated voltage	...	230 V AC	...	100 ... 240 V AC, 50 / 60 Hz
Matrix size	2.1 Mpx	...	2.1 Mpx	...
Maximum power	...	...	...	600 W
Rated current	...	...	...	max. 10 A
Number of buttons	...	...	...	1
Maximal total load	...	<ul style="list-style-type: none"> <li>• 3 x 3680 W (resistance load) - AC,</li> <li>• 3 x 500 W (inductive or capacitive load) - AC,</li> <li>• 3 x 380 W - DC</li> </ul>	...	...
Resolution	1920 x 1080 - 1080p 1280 x 1024 - 1.4 Mpx 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p	...	1920 x 1080 - 1080p	...
Total maximal current	...	3 x 16 A	...	...
Video output	...	...	1 Vpp / 75 Ω - M12, 4-pin socket, Code A	...
Number of inputs	...	3	...	...
Number of outputs	...	3	...	1
Connector type	...	screw terminals	...	screw terminals
Wireless	...	Wi-Fi, 2.4 GHz - IEEE 802.11g	...	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n
OSD menu	...	...	—	—
Vandal-proof	...	...	—	—
Application	...	switching devices on/off	The camera is designed for installation outside vehicles	Works with lighting - switching on/off
Permissible relative humidity	...	...	...	≤ 80 %
Main features	...	<ul style="list-style-type: none"> <li>• Supports max. 3 devices,</li> <li>• Local control by physical button,</li> <li>• schedule,</li> <li>• timer,</li> <li>• sunrise and sunset mode,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• Keyboard built-in - 3 Touch control keys,</li> <li>• Backlit, touch control panel</li> <li>• Omnidirectional antenna</li> <li>Wi-Fi 5 dB,</li> <li>• SMA-RP socket</li> <li>• μWiFi technology support</li> </ul>	...	<ul style="list-style-type: none"> <li>• Local control by physical button,</li> <li>• schedule,</li> <li>• timer,</li> <li>• Setting scenarios by different events,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• LED indication</li> </ul>
Operation temp	...	-20 °C ... 50 °C	...	-20 °C ... 50 °C
Lens	3.6 mm	...	2.8 mm	...
View angle	<ul style="list-style-type: none"> <li>• 83 ° (manufacturer data)</li> <li>• 80 ° (our tests result)</li> </ul>	...	<ul style="list-style-type: none"> <li>91 ° (manufacturer data)</li> <li>86 ° (our tests result)</li> </ul>	...
Range of IR illumination	30 m	...	10 m	...
S/N ratio	> 50 dB	...	≥ 58 dB	...
Memory card slot	—	...	—	...
Image compression method	H.265 / H.264 / MJPEG	...	...	...
Alarm inputs / outputs	—	...	—	...
Audio	—	...	—	...
Bitrate	24 ... 9472 kbps - H.264 14 ... 5632 kbps - H.265	...	...	...
Main stream frame rate	25 fps @ 1920 x 1080	...	...	...
Network interface	10/100 Base-T (RJ-45)	...	...	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Network protocols	HTTP, HTTPS, IPv4/IPv6, TCP, ARP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, QoS, UPnP, NTP, Bonjour, IEEE 802.1x, Multicast, ICMP, IGMP, SNMP	...	...	...
WEB Server	Built-in	...	...	...
Max. number of on-line users	20	...	...	...
ONVIF	16.12	...	...	...
Main features	<ul style="list-style-type: none"> <li>• Motozoom lens</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ICR - Movable InfraRed filter</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• AGC - Automatic Gain Control</li> <li>• Auto White Balance</li> </ul>	...	<ul style="list-style-type: none"> <li>• AGC - Automatic Gain Control</li> <li>• BLC - Back Light Compensation</li> <li>• ICR filter - IR illuminators support</li> <li>• Auto White Balance</li> <li>• Sharpness - sharper image outlines</li> </ul>	...
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) • Android: Free application <a href="#">DMSS</a> , Android: Free application <a href="#">IMOU</a> • iOS (iPhone): Free application <a href="#">DMSS</a> , iOS (iPhone): Free application <a href="#">IMOU</a>	<ul style="list-style-type: none"> <li>• The <a href="#">wBox</a> free application on Android</li> <li>• The <a href="#">wBox</a> free application on iOS</li> </ul>	...	<ul style="list-style-type: none"> <li>• The <a href="#">Tuya Smart</a> free application on Android</li> <li>• The <a href="#">Tuya Smart</a> free application on iOS</li> </ul>
Default IP address	192.168.1.108	...	...	...
Default admin user / password	admin / admin	...	...	...
Web browser access ports	80, 37777	...	...	...
PC client access ports	37777	...	...	...
Mobile client access ports	37777	...	...	...
Port ONVIF	80	...	...	...
RTSP URL	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...	...	...
Color	White	Gray / Black	White	White
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 420 mA</li> </ul>	...	12 V DC / 420 mA - Powering the cameras with 12V DC voltage directly from recorder	...
Power consumption	< 5.4 W	...	< 5 W	...
Housing	Dome - Metal / Plastic	Self-extinguishing , Surface-mounted (box)	Dome, Metal	Plastic
"Index of Protection"	IP67	IP44	...	...
Operation temp	-30 °C ... 60 °C	...	-20 °C ... 60 °C	...
Dimensions	Ø 108 x 84 mm	<ul style="list-style-type: none"> <li>• 129 x 96 x 57 mm - without antenna</li> <li>• 285 x 96 x 57 mm - with antenna, vertical</li> <li>• 197 mm - Antenna</li> </ul>	99 x 97 x 57 mm	87 x 86 x 41 mm
Weight	0.264 kg	0.42 kg	0.28 kg	0.089 kg
Supported languages	English, Polish	...	...	...
Manufacturer / Brand	DAHUA	BleBox	AUTONE	...
Guarantee	3 years	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00