






	RFID PROXIMITY CARD AT10-114N13	CONNECTOR FOR LED STRIPS AD. TL-6499/ZT/RGBW 12 mm QRNO	DOUBLE-SIDED MARKER MARKER.0.5-1.0/BLACK	IP SPEED DOME CAMERA OUTDOOR SD2A500HB-GN-A-PV-S2 - 5 Mpx 4 mm DAHUA	INSULATION STRIPPER HT-352	WIRELESS VIDEO DOORBELL AT10.DBC1- TUYA Wi-Fi_Tuya Smart
						
	6.67 SEK 6.67 SEK	14.69 SEK 14.69 SEK	8.75 SEK 8.75 SEK	2516.67 SEK 2516.67 SEK	114.83 SEK 114.83 SEK	365.33 SEK 365.33 SEK
Standard	...	...	...	TCP/IP	...	...
Material	...	...	...	...	PET	...
Standard	Unique EM 125kHz	...	...	...	...	...
Sensor	...	...	...	1/2.8 " STARVIS™ CMOS	...	Progressive Scan CMOS - 2 Mpx
Compatibility	EM4100/4102	...	...	...	...	...
Matrix size	...	...	...	5 Mpx	...	...
Strip width	...	12 mm	...	...	...	...
Possibility of programming the serial number (ID)	—	...	...	...	...	...
Ability to write to internal memory	—	...	...	...	...	...
Serial Number overprint	✓	...	...	...	...	...
Maximal power voltage	...	48 V	...	...	...	...
IR illuminator	...	...	...	...	...	10 m
LED illuminator	...	...	...	...	...	—
Wireless transmission range	...	...	...	...	...	The range limited only by the availability of the Wi-Fi network
Wi-Fi standard	...	...	...	...	...	IEEE 802.11 b/g/n : 2.4 GHz
Application	...	Works with LED lighting RGBW	Any surface : Wood, Fabric, Glass, Metal, Plastic, Ceramics, CD/DVD discs	...	Cable RG59 , Cable RG6 , Cable RG-7 , Cable RG-11 , Telephone cable 4P / 6P / 8P	...
Ink color	...	...	Black	...	...	...
Resolution	...	...	...	2560 x 1920 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 1080p , 1280 x 960 1.3 Mpx , 1280 x 720 - 720p	...	1920 x 1080 px - 1080p
Main features	• Serial Number Format : 10H13D + WEG24A, • Range : ~ 15 cm, • The TK-4100 chip	...	• high quality • 2 line thicknesses, • round tips : 0.5 mm, 1 mm • waterproof permanent ink	...	• Adjustable stripping blades • High durability tool, made from high quality materials	...
Lens	...	...	...	4 mm	...	2.5 mm
View angle	...	...	...	• 80 ° (manufacturer data) • 77 ° (our tests result)	...	• 135 ° (manufacturer data) • 101 ° (our tests result)
Optical zoom	...	...	...	—	...	...
Digital zoom	...	...	...	—	...	...
Range of IR illumination	...	...	...	30 m	...	...
White light LED illuminator range	...	...	...	30 m	...	...
Video output	...	...	...	—	...	...
Rotation speed (manual control)	...	...	...	0.1 °/s ... 74 °/s (horizontal) 0.1 °/s ... 36 °/s (vertical)	...	...
Preset rotation speed	...	...	...	max. 62 °/s (horizontal) max. 36 °/s (vertical)	...	...
Horizontal rotation range	...	...	...	0 ° ... 345 ° - Rotation of the head is limited by stops	...	...
Vertical rotation range	...	...	...	0 ° ... 80 °	...	...
RS-485 interface	...	...	...	—	...	...
Number of presets	...	...	...	300	...	...
Horizontal scan	...	...	...	—	...	...
Route settings	...	...	...	—	...	...
Image compression method	...	...	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...	H.264 / MJPEG / JPEG
Alarm inputs / outputs	...	...	...	—	...	...
Mount	...	...	...	...	...	Surface-mounted
Main stream frame rate	...	...	...	• 20 fps - 5 Mpx • 25 fps - 4 Mpx	...	...
Memory card slot	...	...	...	Micro SD memory cards up to 512GB support (possible local recording)	...	...
Network interface	...	...	...	10/100 Base-T (RJ-45)	...	Wi-Fi : 2.4 GHz
Network protocols	...	...	...	UDP, FTP, RTMP, IPv4/IPv6, IP Filter, DNS, RTCP HTTP, HTTPS, TCP/IP, NTP, SSL, DHCP, RTP, RTSP, SMTP, DDNS, ARP	...	...
WEB Server	...	...	...	Built-in, NVR compliance	...	...
Max. number of on-line users	...	...	...	20	...	...
ONVIF	...	...	...	21.06	...	...
Audio	...	...	...	• Microphone built-in • Speaker built-in • Audio detection • Bi-directional audio streaming support • Compliance with the AAC standard	...	...
Mobile phones support	...	...	...	Port 37777 • Android: Free application <a href="#">DMSS</a> • iOS (iPhone): Free application <a href="#">DMSS</a>	...	The <a href="#">Tuya Smart</a> free application on Android The <a href="#">Tuya Smart</a> free application on iOS
Default admin user / password	...	...	...	admin / - The administrator password should be set at the first start	...	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Default IP address	...	...	...	192.168.1.108	...	...
Web browser access ports	...	...	...	80, 37777	...	...
PC client access ports	...	...	...	37777	...	...
Mobile client access ports	...	...	...	37777	...	...
Port ONVIF	...	...	...	80	...	...
RTSP URL	...	...	...	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...	...
Main features	...	...	...	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• 2-DNR, 3-DNR - Digital Noise Reduction</li> <li>• Day/night mode</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• ICR - Movable InfraRed filter</li> <li>• The camera is equipped with a built-in heater with a thermostat</li> <li>• Motion Detection</li> <li>• Configurable Privacy Zones</li> <li>• Mirror - Mirror image</li> <li>• Active deterrence function - Light and sound alarm</li> <li>• Smart motion detection (with recognizing people and vehicles)</li> <li>• IVS analysis : intrusion : crossing the line (tripwire)</li> </ul>	...	<ul style="list-style-type: none"> <li>• Micro SD memory cards up to 128GB support (possible local recording).</li> <li>• PIR detector - Motion Detection, Detector range 3 m,</li> <li>• Loitering detection</li> <li>• ICR - Movable InfraRed filter</li> <li>• Auto White Balance</li> <li>• AGC - Automatic Gain Control</li> <li>• BLC - Back Light Compensation,</li> <li>• Microphone built-in,</li> <li>• Speaker built-in,</li> <li>• Bidirectional communication,</li> <li>• Noise and echo reduction</li> <li>• Full support via network : WiFi,</li> <li>• Possibility to work in cloud - you don't need to redirect the ports.</li> <li>• Video PUSH personal messaging</li> <li>• Increased battery life</li> <li>• Low current consumption</li> <li>• Operating frequency - Wireless doorbell : 433 MHz</li> </ul>
Power supply	...	...	...	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 1090 mA</li> </ul>	...	<ul style="list-style-type: none"> <li>• 2 x 18650 battery 3.7 V / 2600 mAh (not included)</li> <li>• 5 V DC - Charging via micro USB port (cable included)</li> </ul>
Power consumption	...	...	...	≤ 13 W	...	...
Housing	...	...	...	Speed Dome, Plastic	...	Waterproof - Plastic
Color	...	White	...	White + Black	...	White / Black
"Index of Protection"	...	...	...	IP66	...	IP66
Operation temp	...	...	...	-30 °C ... 55 °C	...	...
Weight	0.008 kg	0.002 kg	...	0.44 kg	0.14 kg	<ul style="list-style-type: none"> <li>• 0.084 kg - Wireless Video Doorbell</li> <li>• 0.028 kg - mounting base</li> </ul>
Dimensions	86 x 54 x 2 mm	28 x 20 mm	141 x 15 x 11 mm	Ø 111 x 140.5 mm (without bracket)	192 x 45 x 33 mm	<ul style="list-style-type: none"> <li>• 142 x 46 x 32 mm - Wireless Video Doorbell</li> <li>• 158 x 62 x 17 mm - mounting base</li> </ul>
Supported languages	...	...	...	English, Spanish	...	...
Manufacturer / Brand	ATLO	ORNO	...	DAHUA	...	...
Guarantee	2 years	2 years	...	5 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00