



	SMART LED LIGHTING CONTROLLER ATLO-SW1-TUYA Wi-Fi, Tuya Smart	IP SPEED DOME CAMERA OUTDOOR P5AE-PV Picco A2 Wi-Fi - 5 Mpx 4 mm DAHUA
		
	53.73 DKK 53.73 DKK	438.83 DKK 438.83 DKK
Standard	...	IP
Application	switching devices on/off	...
Number of channels	1	...
Maximal total load	250 W	...
Total maximal current	10 A	...
Number of inputs	1	...
Number of outputs	1	...
Connector type	screw terminals	...
Resolution	...	2560 x 1920 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 1080p , 1280 x 720 - 720p
Wireless	<ul style="list-style-type: none"> • Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n • Bluetooth 	...
Radio communication range	< 100 m (open area)	...
Sensor	...	1/2.8 " Progressive Scan CMOS
Lens	...	4 mm
View angle	...	80 °
Optical zoom	...	—
Digital zoom	...	—
Range of IR illumination	...	30 m
White light LED illuminator range	...	30 m
Video output	...	—
Rotation speed (manual control)	...	<ul style="list-style-type: none"> • 0.1 °/s ... 74 °/s (horizontal) • 0.1 °/s ... 36 °/s (vertical)
Preset rotation speed	...	max. 62 °/s (horizontal) max. 36 °/s (vertical)
Main features	<ul style="list-style-type: none"> • Local control by physical button , Tuya Smart : • schedule, • timer, • Setting scenarios by different events, • remote access, • voice control , 	...

Horizontal rotation range	...	0 ° ... 345 ° - Rotation of the head is limited by stops
Operation temp	-10 °C ... 40 °C	...
Vertical rotation range	...	0 ° ... 80 °
RS-485 interface	...	—
Number of presets	...	300
Horizontal scan	...	—
Route settings	...	—
Image compression method	...	H.265+ / H.264 / H.265 / MJPEG / H.264+
Alarm inputs / outputs	...	—
Main stream frame rate	...	25 fps - 5 Mpx
Memory card slot	...	Micro SD card support up to 256GB
Interface	...	<ul style="list-style-type: none"> • Wi-Fi - 2.4 GHz IEEE 802.11 b/g/n, • 10/100 Base-T (RJ-45)
WEB Server	...	Built-in, NVR compliance
Max. number of on-line users	...	20
ONVIF	...	—
Audio	...	<ul style="list-style-type: none"> • Microphone built-in • Speaker built-in • Audio detection • Bi-directional audio streaming support
Mobile phones support	<ul style="list-style-type: none"> • The Tuya Smart free application on Android • The Tuya Smart free application on iOS 	Port 37777 <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Default admin user / password	...	admin / - The administrator password should be set at the first start
Default IP address	...	192.168.1.108
Web browser access ports	...	80, 37777
PC client access ports	...	37777
Mobile client access ports	...	37777
Port ONVIF	...	80
RTSP URL	...	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Intelligent image analysis	...	<ul style="list-style-type: none"> • intrusion • linkage tracking • crossing the line (tripwire)



Main features	...	<ul style="list-style-type: none"> • When Smart Dual Light is active, the white light will turn on automatically only when an object is detected in the monitored area, which effectively improves the image quality • Active deterrence function - Light and sound alarm • Intelligent Object Tracking • Wi-Fi Module - IEEE 802.11 b/g/n, • D-WDR - Wide Dynamic Range • Day/night mode • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • motion detection based on human detection • SMD 3.0 - searching for an object classified as: human, motor vehicle
Power supply	100 ... 240 V AC, 50 / 60 Hz	12 V DC / 1 A
Power consumption	...	≤ 11 W
Housing	Plastic	Speed Dome, Plastic
Color	White	White
"Index of Protection"	IP20	IP66
Operation temp	...	-30 °C ... 55 °C
Weight	0.03 kg	0.44 kg
Dimensions	43 x 39 x 22 mm	Ø 111 x 141 mm (without bracket)
Supported languages	...	English
Manufacturer / Brand	...	DAHUA
Guarantee	2 years	3 years