



	ACCESS CONTROLLER WITH TEMPERATURE MEASUREMENT DS-K1TA70MI-T - 1080p Hikvision	POE SWITCH / EXTENDER PFT1320 3-PORT
		
	1792.85 EUR 1792.85 EUR	17.98 EUR 17.98 EUR
Scanning system	Progressive	...
Resolution	1920 x 1080 - 1080p	...
Sensor	CMOS Uncooled VOx microbolometer	...
LAN ports	...	<ul style="list-style-type: none"> • 1 x RJ45 10/100 Base-T + power input : PoE (802.3af/at), • 2 x RJ45 10/100 Base-T + PoE (802.3af)
Matrix size	2.1 Mpx 120 x 160 px	...
Temperature measurement	✓	...
Temperature measurement range	30 °C ... 45 °C	...
Management	...	—
Accuracy of temperature measurement	± 0.5 °C	...
LED diodes	...	Link, Act
Temperature measurement distance	0.3 ... 1.8 m	...
Transmission speed	...	10 / 100 Mbps
Cards support	13.56 MHz S50	...
Reading distance of prox-keys	~ 5 cm	...
Maximal output power	...	15.4 W @ port PoE - First device
Face recognition distance	0.3 m ... 1.8 m	...
Main features	...	<ul style="list-style-type: none"> • Possibility to connecting in cascade • The device can function as a LAN network and PoE power extender

Memory	Memory of 6000 face templates Memory of 6000 RFID cards Non-volatile log buffer of the last 100 000 events	...
Standard	TCP/IP	...
IR illuminator	✓	...
Range	...	100 m - Input 100 m - Output
LED illuminator	✓	...
Protections	...	—
Video output	—	...
RS-485 interface	✓	...
Memory card slot	—	...
Operation temp. / Relative humidity	...	-30 ... 65 °C / 10 ... 90 %
Alarm inputs / outputs	2 / 1	...
Audio	Speaker built-in	...
Network interface	10/100/1000 Base-T (RJ-45)	...
Network protocols	TCP/IP	...
WEB Server	—	...
ONVIF	—	...
RS-485	✓	...
Default IP address	192.168.1.64	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
PC client access ports	port 8000	...

Main features	<ul style="list-style-type: none"> • Detection of people without a mask - access denied or voice alerts • Temperature measurement • 7 " capacitive touch screen - 1024 x 600 px • Mechanical tamper protection • Wiegand 34/26 • AGC - Automatic Gain Control • Sharpness - sharper image outlines • Day/Night mode (color/b&w/auto) • AI detection : A solution dedicated to measuring temperature. The camera is able to detect increased object temperature 	...
Power supply	12 V DC / 2 A (power adapter not included)	PoE (802.3af/at)
Power consumption	≤ 24 W	0.3 W
Housing	Compact - Metal	Plastic
Color	Silver + Black	...
"Index of Protection"	—	...
Operation temp	0 °C ... 50 °C	...
Weight	1.34 kg	0.05 kg
Dimensions	117 x 290 x 35 mm (without bracket)	88 x 44 x 22 mm
Supported languages	Polish, English, French, Spanish, Portuguese, Russian, Italian	...
Manufacturer / Brand	Hikvision	...
SAP Code	302917212	...
Guarantee	3 years	2 years