





	<a href="#">CABLE GLAND ML-147 IP68 M16 x 1.5</a>	<a href="#">LABEL PRINTER PT-H107 Brother</a>	<a href="#">RUBBER MAT MB-GUM/50</a>	<a href="#">AHD, HD-CVI, HD-TVI HIDDEN CAMERA APTI-H50YK-37 2Mpx / 5Mpx 3.7 mm APTI</a>
				
	0.55 EUR 0.55 EUR	45.04 EUR 45.04 EUR	6.22 EUR 6.22 EUR	29.82 EUR 29.82 EUR
"Index of Protection"	IP68	...	...	...
Display	...	LCD 12 characters	...	...
Type (size)	M16 x 1.5	...	...	...
Standard	...	...	...	AHD, HD-CVI, HD-TVI
Sensor	...	...	...	1/2.7 " CMOS
Cable diameter	Ø 4 ... 8 mm	...	...	...
Matrix size	...	...	...	5 Mpx
Material	Plastic (ABS)	...	...	...
Material	...	...	SBR granulate + polyurethane binder	...
Strip width	...	3.5 mm, 6 mm, 9 mm, 12 mm - TZe type	...	...
Print technology	...	Thermal transfer	...	...
Main features	...	<ul style="list-style-type: none"> <li>• Available fonts: 1</li> <li>• Available frames: 8</li> <li>• Available symbols: 177</li> <li>• Built-in manual cutter</li> <li>• Tape cassette included : 12 mm, Black print on a white background, 4 m</li> </ul>	<ul style="list-style-type: none"> <li>• Rough structure</li> <li>• Granule fraction : 0.5 ... 4 mm</li> <li>• Insulation</li> <li>• High fatigue strength of the material</li> <li>• Weatherproof</li> <li>• Very easy and quick assembly</li> </ul>	...
Resolution	...	...	...	<ul style="list-style-type: none"> <li>• 2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps / 12.5 fps ;</li> <li>• 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 25 fps, 30 fps,</li> <li>• 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 25 fps, 30 fps</li> </ul>
Lens	...	...	...	3.7 mm
View angle	...	...	...	<ul style="list-style-type: none"> <li>• 80 ° (manufacturer data)</li> <li>• 70 ° (our tests result)</li> </ul>
Range of IR illumination	...	...	...	—
Video output	...	...	...	1 Vpp 75 Ω, AHD, HD-CVI, HD-TVI
Alarm inputs / outputs	...	...	...	—
Audio	...	...	...	—

Main features	...	...	...	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• DNR - Digital Noise Reduction</li> <li>• Mirror - Mirror image</li> <li>• Motion Detection</li> <li>• Sharpness - sharper image outlines</li> <li>• Auto White Balance</li> </ul>
OSD menu	...	...	...	OSD - with the in-line remote control
Application	...	...	<ul style="list-style-type: none"> <li>• Area covering,</li> <li>• Soundproofing</li> </ul>	For indoor use
Power supply	...	6 x 1.5V, type AAA/LR03 battery	...	12 V DC / 70 mA
Power consumption	...	...	...	≤ 0.8 W
Housing	...	...	...	Spy - Plastic
Color	...	...	Black	White
Operation temp	...	...	...	-10 °C ... 50 °C
Weight	0.007 kg	0.39 kg	2.4 kg	0.12 kg
Dimensions	33 x 24 x 24 mm	207 x 110 x 59 mm	500 x 500 x 10 mm	119 x 69 x 48 mm
Supported languages	...	...	...	Polish, English French Spanish, Portuguese, Russian, Italian
Manufacturer / Brand	...	Brother	...	APTI
Guarantee	...	3 years	...	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00