




	EXTENDER ETHERNET+PoE LR1002-1ET TRANSMITTER DAHUA	AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE56D0T- IRMMF(3.6mm) - 1080p Hikvision	SMART GATE AND DOOR CONTROLLER GATEBOX/BLEBOX Wi-Fi, 12 ... 24 V DC/AC
			
	56.78 USD 56.78 USD	49.23 USD 49.23 USD	48.49 USD 48.49 USD
LAN ports	1 pcs RJ45
Application	swing gates, sliding gates, garage gates, doors
Transmission ports	1 pcs BNC
Rated voltage	12 ... 24 V DC/AC
Transmission speed	10 / 100 Mbps Full Duplex
Standard	...	AHD / HD-CVI / HD-TVI / PAL	...
Maximal total load	—
Sensor	...	Progressive Scan CMOS	...
Matrix size	...	2.1 Mpx	...
Total maximal current	20 mA / Control output
Number of inputs	2
Resolution	...	1920 x 1080 - 1080p	...
Number of outputs	2
Transmission range	max. 1000 m @ 10 Mbps max. 400 m @ 100 Mbps The range of data transfer and power supply is strongly dependent on the cable used and the power required to supply the receiver
Range of IR illumination	...	20 m	...
Connector type	screw terminals
Protections	Overvoltage
IR illuminator power adjustment	...	Automatic	...
Lens	...	3.6 mm	...
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11g
Mobile phones support	<ul style="list-style-type: none"> • The wBox free application on Android • The wBox free application on iOS

View angle	...	<ul style="list-style-type: none"> • 82 ° (manufacturer data) • 78 ° (our tests result) 	...
IR illuminator support	...	ICR - Movable InfraRed filter	...
S/N ratio	...	> 62 dB	...
Video output	...	1 Vpp / 75 Ω - AHD / HD-CVI / HD-TVI, BNC socket	...
Main features	<ul style="list-style-type: none"> • Plug & Play • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Support for IP cameras and network devices • Easy installation - doesn't require any configuration of IP nor MAC address • The device operates from the camera side • Possibility to mount on a wall, or on the DIN TS-35 rail • UTP cable length to the camera max. 2 m 	...	<ul style="list-style-type: none"> • Control of the electric strike and automatic gate, • Multiple users support from anywhere, • Control many objects from one app, • remote access, • voice control, • µWiFi technology support
Main features	...	<ul style="list-style-type: none"> • DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Day/night mode • BLC - Back Light Compensation • Auto White Balance 	...
Operation temp	-20 °C ... 50 °C
OSD menu	...	—	...
Power supply	<ul style="list-style-type: none"> • ePoE • PoE (802.3af/at) 	12 V DC / 330 mA	...
Power consumption	...	≤ 4 W	...
Housing	...	Dome, Plastic	Plastic
Color	...	White	Black
Vandal-proof	...	—	...
"Index of Protection"	...	IP44	IP20
Operation temp	...	-20 °C ... 45 °C	...
Weight	0.061 kg	0.15 kg	0.03 kg
Dimensions	79 x 64 x 23 mm	Ø 98 x 66 mm	50 x 34 x 18 mm
Manufacturer / Brand	DAHUA	Hikvision	BleBox
SAP Code	...	300609197	...
Guarantee	3 years	3 years	2 years