

	MOUNTING PLATE FX2-DIN KEYSTONE DIN TS-35	SWITCH POE TL-SG3428MP 24-PORT SFP TP-LINK
		
	1.93 GBP 1.93 GBP	426.15 GBP 426.15 GBP
Place for connectors	2 pcs	...
Material	Metal	...
Color	Silver	...
Application	DIN rail (TS-35)	...
LAN ports	...	<ul style="list-style-type: none"> • 24 x RJ45 10/100/1000 Base-TX + PoE (802.3af/at), • 4 x port SFP - Uplink 1000 Base-X, • 1 x RJ45 - Console
Management	...	✓
Transmission speed	...	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps - 24 LAN & PoE ports, • 1000 Mbps - 4 SFP ports
Maximal output power	...	30 W / port PoE
Maximal total power	...	384 W
Jumbo Frame	...	9 kB
MAC addresses table	...	8k

Main features	...	<ul style="list-style-type: none"> • Omada Central Management System • Switch is managed via a web browser, command line interface and SNMP, RMON protocols • CoS/DSCP priority based on IEEE 802.1p standard • Queue scheduling: SP, WRR, SP+WRR • Port/flow-based rate limiting • IEEE 802.1Q VLAN, Port Based VLAN, MAC Based VLAN, Private VLAN support • IEEE 802.1Q standard support, up to 4096 VLAN groups and 4K VIDs • GVRP (GARP VLAN Registration Protocol) support • IGMP Snooping V1/V2/V3 • Spanning Tree STP/RSTP/MSTP • BPDU Filtering/Guard • TC / Root Protect • Loop back detection • Data Flow Control (802.3x) • Storm Control function • Static routing • Static link aggregation • Port mirroring function • DHCP snooping support • Multicast • Hardware supports IP + MAC binding based on port • Access Control List - L2/L4 ACL package filtering based on source and destination MAC addresses • IEEE 802.1x and Radius Authentication • Support DoS defence • Port Security • IPv6 compliance • SSL, SSH • Console : RJ-45 output, micro USB
LED diodes	...	Power, System, PoE Max, Fan, Speed, PoE
Housing	...	Metal
Operation temp	...	0 °C ... 45 °C
Certificates	...	CE, FCC, RoHS



Power supply	...	100 ... 240 V AC
Power consumption	...	max. 31 W max. 463.8 W (PoE 384 W)
Weight	0.054 kg	5 kg
Dimensions	52 x 50 x 42 mm	440 x 335 x 44 mm, RACK 19", 1U
Manufacturer / Brand	...	TP-LINK
Guarantee	2 years	5 years