


	<a href="#">POWER DISTRIBUTION UNIT ACAR-XPROTECTOR</a>	<a href="#">POWER DISTRIBUTION UNIT ACAR-SMART (6 OUTLETS)</a>
		
	20.08 EUR 20.08 EUR	21.89 EUR 21.89 EUR
Rated voltage	230 V AC / 50 Hz	230 V AC / 50 Hz
Total maximal current	10 A	...
Protection level	...	≤ 1.3 kV
Maximal total load	2300 W	...
Nominal load current	...	10 A (total)
Number of outlets	5 grounded outlets 10A/250V	...
Response time	< 25 ns	< 25 ns
Number of output outlets	...	6
Automatic delayed fuse	10 A / 250 V	...
Leak current	< 0.5 mA	< 0.5 mA
Nominal voltage of surge suppressor	250 V / 50 Hz	...
Protection level of surge suppressor	≤ 1.3 kV (L/N)	...
Nominal stroke current	1 kA (L/N) - (8/20μs)	2 kA (L/N) 8/20 μs 8/20 μs
Switch	two-way, with light indication	2 pcs
Maximum stroke current	4.5 kA (L/N) - (8/20μs)	6.5 kA (L/N)
Length of the cable	1.45 m	1.4 m
Housing	Plastic - non-flammable	Plastic - non-flammable
Dimensions	365 x 65 x 52 mm	138 x 100 x 63 mm
Weight	0.51 kg	0.4 kg
Guarantee	2 years	2 years