




	PROJECTOR MOUNT MC-515S	MULTI-SOCKET PLUG WITH SURGE PROTECTION ACAR-MINI-AGD	POWER DISTRIBUTION UNIT WITH REMOTE CONTROL OR-AE-13132 (5 OUTLETS) ORNO
			
	16.67 EUR 16.67 EUR	9.94 EUR 9.94 EUR	41.99 EUR 41.99 EUR
Bearing capacity	10 kg
Rated voltage	...	230 V AC / 50 Hz	230 V AC / 50 Hz
Total maximal current	...	10 A	10 A
Distance from mounting surface	100 mm or 170 mm from ceiling
Maximal total load	...	2300 W	2300 W
Response time	...	< 25 ns	...
Projector mounting holes distances	Ø 130 ... 320 mm
Number of outlets	...	2 grounded outlets 10A/250V	5 grounded outlets 10A/250V
Socket type	CEE 7/5 E type
Maximal voltage	...	250 V / 50 Hz	...
Plug type	CEE 7/7
Tilt adjustment	-15 ° ... 15 °
Horizontal rotation	360 °
Protection level of surge suppressor	...	≤ 1.3 kV (L/N)	...
Switch	—
Length of the cable	3 m
Nominal stroke current	...	2 kA (L/N) - (8/20µs)	...
Maximum stroke current	...	10 kA (L/N) - (8/20µs)	...
Electric shock protection system	...	Ground connectors (pins) connected with ground wire of AC mains	...
Wireless	<ul style="list-style-type: none"> • 433.92 MHz • Remote control • Operating range in open area : 30 m

Main features	<ul style="list-style-type: none"> • radio remote controller in the set • Remote controlled : Supports max. 5 devices • LED indicators displaying the device's operating status • Overload protection • Current paths shutters • Insulation - PVC • Wire gauge : 3 x 1.5 mm² • "Index of Protection" : IP20
Housing	...	Plastic - non-flammable	Plastic
Color	Silver	...	Black
Power supply	<ul style="list-style-type: none"> • 230 V AC, 50 Hz • Remote control : 12V, type A23 battery (included)
Weight	0.96 kg	0.12 kg	0.92 kg
Dimensions	max. Ø 320 x 170 mm	131 x 55 x 75 mm	390 x 68 x 45 mm
Manufacturer / Brand	ORNO
Guarantee	2 years	2 years	2 years