




|                                     | <a href="#">POWER CORD CABLE<br/>IEC320-C13/IEC320-C14/1.8M<br/>1.8 m LANBERG</a>   | <a href="#">TV OR MONITOR MOUNT<br/>BRATECK-LPA52-466</a>                         | <a href="#">BUFFERED POWER SUPPLY<br/>ADAPTER AD-55A MEAN<br/>WELL</a>                         |
|-------------------------------------|---|---|--|
|                                     |    |  |             |
|                                     | 3.20 EUR<br>3.20 EUR  | 15.62 EUR<br>15.62 EUR  | 39.24 EUR<br>39.24 EUR   |
| Adapter type                        | ...   | ...   | Switching  |
| Cable                               | IEC320 C13 socket / IEC320 C14 plug   | ...   | ...  |
| Length of the cable                 | 1.8 m   | ...   | ...  |
| Power voltage                       | ...   | ...   | 100 ... 240 V AC   |
| Voltage                             | max. 250 V  | ...   | ...  |
| Output voltage                      | ...   | ...   | 13.8 V DC  |
| Current                             | max. 2.5 A  | ...   | ...  |
| Output voltage adjustment           | ...   | ...   | 12 ... 14.5 V  |
| Maximal load                        | ...   | ...   | 3.5 A  |
| Battery charging current            | ...   | ...   | 0.23 A   |
| Output power                        | ...   | ...   | 50 W   |
| Main features                       | <ul style="list-style-type: none"> <li>• 100% copper conductor</li> <li>• Very easy and quick assembly</li> <li>• Solid workmanship</li> <li>• 3 x 0.75 mm<sup>2</sup></li> </ul> | ...   | ...  |
| Efficiency                          | ...   | ...   | 71 %   |
| Mounting standard                   | ...   | VESA : 75, 100, 200, 300, 300x200, 400x200, 400, 600x200, 600x400                 | ...  |
| Number of outputs                   | ...   | ...   | 1 pcs  |
| Screen size range                   | ...   | 37 " ... 70 "   | ...  |
| Protections                         | ...   | ...   | <ul style="list-style-type: none"> <li>• Overvoltage</li> <li>• Overload protection</li> </ul> |
| Bearing capacity                    | ...   | 40 kg   | ...  |
| Distance from mounting surface      | ...   | 53 ... 464 mm   | ...  |
| Color                               | ...   | Black   | ...  |
| Operation temp. / Relative humidity | ...   | ...   | -10 °C ... 50 °C / 20 % ... 90 %   |
| Tilt adjustment                     | ...   | -15 ° ... 5 °   | ...  |
| Supported standards                 | ...   | ...   | UL60950-1, TUV EN60950-1   |
| Horizontal rotation                 | ...   | -60 ° ... 60 °  | ...  |
| EMI conduction and radiation        | ...   | ...   | Compliance to EN55022 (CISPR22) class B  |

|                                     |          |                             |  |
|-------------------------------------|----------|-----------------------------|--|
| Harmonic                            | ...      | ...                         | Compliance to EN61000-3-2,-3 standard  |
| Rotation in the plane of the screen | ...      | -3 ° ... 3 °                | ...  |
| EMS immunity                        | ...      | ...                         | Compliance with EN61000-4-2, 3, 4, 5, 6, 8, 11, ENV50204, EN55024, EN61000-6-1 standards |
| Weight                              | 0.162 kg | 4.72 kg                     | 0.45 kg  |
| Dimensions                          | ...      | 655 x 420 x (53 ... 464) mm | 160 x 97 x 38 mm   |
| Manufacturer / Brand                | LANBERG  | BRATECK                     | MEAN WELL  |
| Guarantee                           | 2 years  | 2 years                     | 2 years  |