

	POE SWITCH WITH BUFFERED POWER SUPPLY IPUPS-8-20-H 8-PORT ATTE	RFID PROXIMITY KEY-FOB ATLO-544N/B	NVR BCS-B-NVR0801-8P(2.0) 8 CHANNELS, 8 PoE BCS BASIC
			
	135480.77 HUF 135480.77 HUF	225.00 HUF 225.00 HUF	54326.92 HUF 54326.92 HUF
Standard	TCP/IP
Standard	...	Unique EM 125kHz	...
Compatibility	...	EM4100/4102	...
Supported resolutions	max. 8 Mpx 4K UHD - 3840 x 2160 px
Serial Number overprint	...	✓	...
Possibility of programming the serial number (ID)	...	—	...
Video outputs	1 pcs HDMI 4K 1 pcs VGA
Ability to write to internal memory	...	—	...
Color	...	Black	...
Audio support	8 Channels - Audio from cameras
LAN ports	<ul style="list-style-type: none"> • 2 x RJ45 10/100/1000 Base-T - Uplink, • 8 x RJ45 10/100 Base-T + PoE (802.3af/at) / Passive PoE
Audio inputs	—
Audio outputs	1 pcs CINCH
Management	—
Image compression method	H.265+ / H.265 / H.264+ / H.264
Bitrate	max. 50 Mbps
Supported hard drives	1 x 6 TB SATA
LED diodes	AC, DC, CHARGING (battery charging), PoE, Gigabit Ethernet
Recording modes	Manual, Motion Detection, Schedule
External storage devices backup	Backup to USB drive (pendrive, external drive)
Searching and playback the records	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) 1/4/9 channel synchronous playback

Transmission speed	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps : 2 x Port Uplink, • 10 / 100 Mbps : 8 x Port LAN & PoE
Network interface	1 x RJ-45 10/100/1000 Base-TX
Network functions	Full support via network, Remote records copying, Web-Server built-in max. 128 on-line users
Maximal output power	<ul style="list-style-type: none"> • 40 W @ Passive PoE - LAN1 ... LAN8 ports, • 30 W @ PoE (802.3af/at) - LAN1 ... LAN8 ports
Maximal total power	60 W
Network protocols	P2P, UPnP, DHCP
ONVIF	✓
Default admin user / password	admin / 123456
Operation modes	Standard : 100 m @ 10/100 Mb/s - LAN1 ... LAN8 ports
Default IP address	DHCP or 192.168.1.30
Web browser access ports	80, 554
PC client access ports	Port no.: 80 or access by a cloud (P2P)
Mobile client access ports	80
Mobile phones support	Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application BCS Manager • iOS (iPhone): Free application BCS Manager
RTSP URL	rtsp://192.168.1.30:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.30:554/unicast/c1/s1/live - Sub stream
Alarm inputs / outputs	—
PTZ control	IP Speed Dome Cameras
Motion Detection	✓
USB	2 x USB 2.0
Mouse support	✓
IR remote controller in the set	—
Switch PoE	8-port PoE Switch built-in, 30 W / Channel, PoE (802.3af/at)
Maximum total switch load	75 W
Power consumption	max. 9 W (without HDD)

Main features	<ul style="list-style-type: none"> • 4K UHD support • The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 8 ports • The modular design streamlines service tasks and enables quick and easy system expansion • The raster system of module assembly facilitates the expansion of the device by further modules • 2 x Place for battery : 12 V / 18 Ah • Place for recorder (NVR) • Battery charging current : 1 A / 2 A - (set with the JP1 jumper) • Battery - Protection against reverse polarity connection, Protection against deep discharge of the battery • Technical outputs of the OC type signaling loss of voltage at the PSU output (OUF) and loss of voltage in the 230V mains (ACF) • PSU thermal protection : 130 °C • Overload protection • LAN & PoE ports - Short-circuit protection, Overvoltage • TAMPER switch indicating open the cover • "Index of Protection" : IP20 	<ul style="list-style-type: none"> • The TK-4100 chip • Serial Number Format : 8H10D 	...
Power supply	190 ... 260 V AC	...	52 V DC / 1.8 A (power adapter included)
Weight	4.40 kg	0.005 kg	0.97 kg
Dimensions	455 x 405 x 150 mm	44 x 31 x 5 mm	260 x 243 x 46 mm
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovak, Italian
Manufacturer / Brand	ATTE	ATLO	BCS BASIC
Guarantee	3 years	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00