



	<a href="#">SWITCH POE GTX-A1-10-82 8-PORT</a>	<a href="#">LIVE WIRE, METAL AND WOOD DETECTOR UT-387B UNI-T</a>
		
	270.40 PLN 270.40 PLN	216.52 PLN 216.52 PLN
LAN ports	<ul style="list-style-type: none"> <li>• 8 x RJ45 ( 1 x Hi-PoE + 7 x PoE (802.3af/at) ),</li> <li>• 2 x RJ45 - Uplink</li> </ul>	...
Detector range	...	<ul style="list-style-type: none"> <li>• Wood : 20 mm,</li> <li>• Metal : 80 mm,</li> <li>• AC live wires : 50 mm</li> </ul>
Management	—	...
LED diodes	Power, V - VLAN (Port Isolation), S - Extend, PoE, Link/Act	...
Manufacturer / Brand	...	UNI-T
Transmission speed	10 / 100 Mbps : 2 x Port LAN - Uplink + 8 x Port LAN & PoE	...
Operation modes	<ul style="list-style-type: none"> <li>• N - Normal - the device operates as normal PoE switch</li> <li>• V - VLAN (Port Isolation) - 1 ... 8 ports are isolated from each other and separately work with the 9, 10 ports</li> <li>• S - Extend - Range : 250 m @ 10 Mbps</li> </ul>	...
Maximal output power	<ul style="list-style-type: none"> <li>• 60 W / port Hi-PoE - Port 1</li> <li>• 30 W / port PoE - 2 ... 8 ports</li> </ul>	...
Maximal total power	120 W	...
MAC addresses table	1k	...

Main features	<ul style="list-style-type: none"> <li>• MDI/MDI-X auto detection feature - auto detecting the data transmission mode</li> <li>• Full Duplex: IEEE802.3x, Half Duplex: Back Pressure</li> <li>• Auto-learning and Auto-aging functions support for MAC addresses</li> <li>• PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected</li> <li>• MTBF (Mean Time Between Faults) : 50000 h</li> </ul>	<ul style="list-style-type: none"> <li>• Automatic calibration after turned on,</li> <li>• Optical - sound signaling,</li> <li>• ZOOM function - More precise location of small metal elements with visualization of their location</li> </ul>
Certificates	CE, FCC Class B	...
Protections	Overvoltage $\pm$ 4 kV	...
Power supply	100 ... 265 V AC	9V, type 6F22 battery - included
Operation temp	-10 °C ... 45 °C	...
Weight	0.76 kg	0.23 kg - Without batteries
Dimensions	210 x 150 x 35 mm	220 x 83 x 36 mm
Guarantee	2 years	2 years