






	ACCESS CONTROLLER MC16-PAC-ST-1-KIT ROGER	SMART LED LIGHTING CONTROLLER WLIGHTBOX- PRO/BLEBOX Wi-Fi, 12 ... 24 V DC	PROJECTOR MOUNT BRATECK-PRB-3	WALL MOUNTING KIT USP- U30 FOR SOLAR PANELS	CLEANING PASTE PEVALIN- PROFESSIONAL/250 TUBE 250 ml TESA
					
	352.95 EUR 352.95 EUR	39.25 EUR 39.25 EUR	17.69 EUR 17.69 EUR	23.96 EUR 23.96 EUR	8.20 EUR 8.20 EUR
Material	Aluminum	...
Bearing capacity	10 kg
Number of served transitions	1 (two-way)
Package	Tube 250 ml
Number of supported readers	4
Tilt angle adjustment:	15 ° ... 50 °	...
Application	...	Works with LED lighting - (RGB/RGBW/RGBCCT/CCT/MONO) 12-24V LED strips
Number of users	unlimited (purchase of the appropriate license required)
Rated voltage	...	12 ... 24 V DC
Distance from mounting surface	130 or 440 or 750 or 1075 mm
Maximal total load	...	288 W
Number of media per ID	8 - Proximity card, PIN code, fingerprint, etc.
Projector mounting holes distances	Ø 130 ... 320 mm
Buffer memory	8 000 000 events buffer
Number of access zones	4
Tilt adjustment	-15 ° ... 15 °
Number of alarm zones	4
Total maximal current	...	12 A (3 A / Channel)
Horizontal rotation	360 °
Number of inputs	...	1
Battery backup support	12 V / 20 Ah
Number of outputs	...	4
Connector type	...	screw terminals
Communication	• Ethernet - RJ-45 socket • RACS 5 v2 (Roger) • RS-485 interface
Wireless	...	Wi-Fi, 2.4 GHz - IEEE 802.11g
Mobile phones support	...	• The wBox free application on Android • The wBox free application on iOS
Power supply	• 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC
Permissible relative humidity	10 % ... 95 % (non- condensing)

Main features	<ul style="list-style-type: none"> • Metal housing • Integrated support in VISO ST software • Functions in the VISO ST system: <ul style="list-style-type: none"> - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system : 128 	<ul style="list-style-type: none"> • Local control by physical button, • schedule, • timer, • sunrise and sunset mode, • remote access, • voice control, • Controlling the color, color temperature, brightness, effect, changing time allows any interior arrangement • predefined effects, • effects modification, • Operation modes : <ul style="list-style-type: none"> - 1 x RGB (color) - 1 x RGBW (color + white - brightness control) - 1 x RGB (color) + 1 x MONO (white) - 1 x CCT (white - brightness and color temperature control) - 2 x CCT (white - brightness and color temperature control) - 4 x MONO (single color) / halogen bulb • Omnidirectional antenna Wi-Fi 5 dB, • SMA-RP socket • µWiFi technology support 	...	Maximum power of the mounted panel : 80 W	...
Housing	...	<ul style="list-style-type: none"> • Non-halogen plastic, Self-extinguishing • Waterproof, Weatherproof
"Index of Protection"	...	IP54
Color	...	Black	Silver
Operation temp	5 °C ... 40 °C	-20 °C ... 50 °C
Weight	3.9 kg	0.1 kg	2.1 kg	0.94 kg (total)	...
Dimensions	405 x 365 x 120 mm	<ul style="list-style-type: none"> • 92 x 52 x 28 mm - without antenna • 230 x 85 x 28 mm - with antenna, vertical • 197 mm - Antenna 	max. Ø 320 x 1075 mm	310 x 300 x 43 mm - each item	...
Manufacturer / Brand	ROGER	BleBox	BRATECK	...	TESA
Guarantee	3 years	2 years	2 years	2 years	2 years