

	ACCESS POINT ENCLOSURE NHD-COVER- BLACK-3.3 PCS SET UBIQUITI	IP CAMERA DS-2CD2086G2-(2.8MM)(C) ACUSENSE - 8.3 Mpx Hikvision	BRANCH JUNCTION BOX WITH CABLE GLANDS PK-255X200	STYROFOAM PLUG FISCHER FID-90	POWER GENERATOR DY-1020/PRO 800 W Dynamo
					
	743.20 NOK 743.20 NOK	3966.54 NOK 3966.54 NOK	90.66 NOK 90.66 NOK	14.17 NOK 14.17 NOK	3274.42 NOK 3274.42 NOK
In package	3 pcs
Standard	...	TCP/IP
Nominal power	800 W
Length	90 mm	...
Number of intakes	12 pcs Ø 32 mm
Sensor	...	1/1.8 " Progressive Scan CMOS
Diameter	Ø 25 mm	...
Scanning system	...	Progressive
Thickness of the Styrofoam	≥ 90 mm	...
Diameter of the screw	Ø 6 mm	...
Matrix size	...	8.3 Mpx
Support	UNIFI-NANOHD, UNIFI-U6-LITE, UNIFI-U6+, UNIFI-UAP-AC-LITE
Maximum power	1000 W
Tamper protection	—
Output voltage	230 V AC
Number of outlets	1 pcs - single-phase
Built-in voltmeter	✓
Material	Plastic (polycarbonate)
Output frequency	50 Hz
Voltage stabilization	AVR
Frequency measurement in Hz	✓
Measuring the number of engine hours	✓
12V DC output	✓
Alternator windings	Copper
Engine power	3.5 HP
Engine capacity	98 cm ³
Resolution	...	3840 x 2160 - 8.3 Mpx , 3200 x 1800 - 5 Mpx , 2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens	...	2.8 mm
Engine type	1 cylinder, 4 stroke, gasoline, air cooled
Starting the engine	Manual
View angle	...	• 111 ° (manufacturer data) • 106 ° (our tests result)
Noise level during operation	92 dB
Compression	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Average fuel consumption	0.75 l/h - 50 % power
Range of IR illumination	...	40 m
Fuel tank capacity	6 l
Alarm inputs / outputs	...	—
Fuel gauge	✓
Audio	...	—
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)
Main stream frame rate	...	25 fps @ 8.3 Mpx
Network interface	...	10/100 Base-T (RJ-45)
Network protocols	...	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, IEEE 802.1x, QoS, IPv4, IPv6, UDP, Bonjour, SSL / TLS, PPPoE, SNMP, ARP
WEB Server	...	Built-in
Max. number of on-line users	...	6
ONVIF	...	18.12
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • iOS: Free application Hik-Connect
Default IP address	...	192.168.1.64

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80
PC client access ports	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	...	8000
Port ONVIF	...	80
RTSP URL	...	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/
RS-485 interface	...	—
Main features	...	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • Possibility to change the resolution, quality and bit rate • ICR - Movable InfraRed filter • Configurable Privacy Zones • Motion Detection • Mirror - Mirror image • Filtering of false alarms based on the recognition of persons and vehicles • Intelligent image analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area, classification of people and vehicles, scene changing, face detection, advanced face capture features
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 500 mA
Power consumption	...	<ul style="list-style-type: none"> • ≤ 7.2 W @ PoE (802.3af) • ≤ 6 W @ 12 V DC
Housing	...	Compact, Metal
Color	Matt black	White	Red + Black
"Index of Protection"	...	IP67	IP65
Operation temp	...	-30 °C ... 60 °C
Supported languages	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Vietnamese, Italian
Weight	0.068 kg	0.48 kg	...	0.012 kg	27.08 kg
Dimensions	Ø 169 x 34 mm	Ø 70 x 162 mm	255 x 200 x 77 mm	...	485 x 365 x 420 mm
Manufacturer / Brand	UBIQUITTI	Hikvision	Dynamo
SAP Code	...	311315446
Guarantee	2 years	3 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00