



	<a href="#">TV OR MONITOR MOUNT BRATECK-LP42-69T</a>	<a href="#">SEPARATOR WITH VIDEO BALUN D-SEP/HD-4/TR</a>
		
	20.53 EUR 20.53 EUR	24.57 EUR 24.57 EUR
Standard	...	<ul style="list-style-type: none"> <li>• AHD - 8 Mpx, 4K UHD</li> <li>• HD-CVI - 8 Mpx, 4K UHD</li> <li>• HD-TVI - 8 Mpx 4K UHD</li> <li>• CVBS - PAL / NTSC</li> </ul>
Mounting standard	VESA 75, 100, 150, 200, 200x100, 300, 400x200 400x300, 400, 600x400, 600, 800x600, 900x600	...
Screen size range	60 " ... 100 "	...
Bearing capacity	75 kg	...
Distance from mounting surface	85 mm	...
Color	Black	...
Tilt adjustment	-10 ° ... 5 °	...
Video transmission range	...	<ul style="list-style-type: none"> <li>• 250 m @ 720p - UTP cat. 5e</li> <li>• 150 m @ 1080p - UTP cat. 5e</li> <li>• 400 m @ CVBS - PAL / NTSC - UTP cat. 5e</li> </ul>
Device type	...	Passive
Number of channels	...	4 pcs Video
Number of inputs	...	4 pcs cable terminals
Number of outputs	...	4 pcs BNC socket
Input impedance	...	100 Ω
Output impedance	...	75 Ω
Opto-isolation between inputs and outputs	...	50 V DC
Galvanic separation between individual channels	...	> 2000 V
Attenuation	...	<ul style="list-style-type: none"> <li>• 4.43 MHz @ 0.34 dB</li> <li>• 11 MHz @ 0.49 dB</li> <li>• 21 MHz @ 0.71 dB</li> <li>• 38 MHz @ 1.00 dB</li> <li>• 42 MHz @ 1.08 dB</li> <li>• 67.5 MHz @ 1.70 dB</li> </ul> <p>The attenuation applies to two devices connected to each other</p>
Bandwidth	...	200 MHz

CMRR (dB @ 5MHz)	...	50 dB
Inputs protection	...	ESD, IEC 61000-4-2, ±30kV contact, ±30kV air EFT, IEC 61000-4-4, 40A (5/50ns) Lightning, IEC 61000-4-5, 30A (t <sub>p</sub> =8/20µs)
Power supply	...	—
Operation temp	...	-20 °C ... 55 °C
Weight	3.7 kg	0.09 kg
Dimensions	954 x 625 x 85 mm	103 x 75 x 30 mm
Manufacturer / Brand	...	DELTA
Guarantee	2 years	3 years