

	DOORBELL BUTTON PD-1 ORNO	MODULAR BELL LE-004107 LEGRAND	ANGULAR COUPLER LMA-LX50/B	WIRELESS VIDEO DOORBELL ATLO-DBCT-TUYA-V2 Wi-Fi, Tuya Smart	FLUSH BOX 3-GANG P-3X60-D SIMET
					
	1597.12 HUF 1597.12 HUF	9921.15 HUF 9921.15 HUF	721.15 HUF 721.15 HUF	19234.62 HUF 19234.62 HUF	1702.88 HUF 1702.88 HUF
Length	100 mm
Device type	...	Bell
Width	100 mm
Number of sections	3
Sensor	CMOS - 2 Mpx	...
Depth	27.5 mm
Rated voltage	...	230 V AC, 50 / 60 Hz
Current consumption	...	23 mA
Resolution	1920 x 1080 px - 1080p	...
Lens	3.6 mm	...
"Index of Protection"	IP44	IP30
Operation state indication	...	—
Connectors type	...	screw terminals
View angle	• 120 ° (manufacturer data) • 98 ° (our tests result)	...
IR illuminator	✓	...
LED illuminator	—	...
Wireless transmission range	The range limited only by the availability of the Wi-Fi network	...
Wi-Fi standard	2.4 GHz IEEE 802.11 b/g/n	...
Width in 17.5 mm modules	...	1
Network interface	2.4 GHz Wi-Fi	...
Main features	Housing - Plastic, Surface-mounted	Provided space for a label with description	<ul style="list-style-type: none"> • Flush-mounted for hollow walls • stiffened construction • flammability index : 960 °C • Class V0 • 3 x 4 fixing points • 6 mounting screws, 4 special screws with holders to fastening to the wall, 4 cable partitions - included
Mobile phones support	The Tuya Smart free application on Android The Tuya Smart free application on iOS	...
Material	PVC	...	halogen free and inflammable
Mounting holes distance	60 mm
Manufacturer / Brand	ORNO	LEGRAND	SIMET

Main features	<p>Doorbell button + Camera</p> <ul style="list-style-type: none"> • The microSD cards support 128 GB - Video recording to micro SD card, • Motion Detection - PIR detector, • ICR - Movable InfraRed filter, • Microphone built-in, • Speaker built-in, • Bidirectional communication, • Full support via network : WiFi, • Possibility to work in cloud - you don't need to redirect the ports, • Video PUSH personal messaging • Increased battery life • Low current consumption <p>Wireless doorbell</p> <ul style="list-style-type: none"> • Operating frequency 433 MHz • Volume ≤ 100 dB • Selecting the ringer melody • Number of ring-tones : 60 • 5-level ring tone volume adjustment • LED indicator 	...
Mount	Surface-mounted	...
Power supply	max. 250 V / 1 A	<p>Doorbell button + Camera</p> <ul style="list-style-type: none"> • 2 x 18650 battery 3.7 V / 3200 mAh (not included) • Charging via micro USB port 5 V DC (cable included) <p>Wireless doorbell</p> <ul style="list-style-type: none"> • 90 ... 260 V AC 	...
Power consumption	...	4 VA	...	0.15 W (operation), ≤ 10 mW (Standby mode) - Wireless doorbell	...
Housing	...	Plastic, DIN, TS-35 rail mounting	...	Plastic	...
Color	Black	White / Black	Blue
Weight	0.035 kg	0.061 kg	0.03 kg	<ul style="list-style-type: none"> • 0.128 kg - Doorbell button + Camera • 0.050 kg - Wireless doorbell 	0.131 kg
Dimensions	81 x 33 x 20 mm	66 x 83 x 18 mm	...	<ul style="list-style-type: none"> • 145 x 51 x 38 mm - Doorbell button + Camera • 70 x 51 x 68 mm - Wireless doorbell 	214 x 71 x 63 mm
Guarantee	2 years	2 years	2 years	2 years	2 years