




	<a href="#">IP CAMERA IPC-HFW3549T1-ZAS-PV-27135 TiOC Full-Color - 5 Mpx 2.8 ... 13.5 mm - MOTOZOOM DAHUA</a>	<a href="#">MULTIMEDIA SHELF AX-RTV1</a>	<a href="#">ACCESS POINT +ROUTER ARCHER-VR300 VDSL / ADSL 2.4 GHz, 5 GHz 300 Mbps + 867 Mbps TP-LINK</a>
			
	849.39 CAD 849.39 CAD	14.06 CAD 14.06 CAD	93.50 CAD 93.50 CAD
Standard	TCP/IP	...	...
Number of shelves	...	1	...
Sensor	1/2.7 " Progressive Scan CMOS	...	...
Bearing capacity	...	10 kg	...
Frequency range	...	...	2.4 GHz, 5 GHz
Matrix size	5 Mpx	...	...
Swivel angle adjustment:	...	—	...
Antenna type	...	...	4 x Omnidirectional antenna 5 dBi
Distance from mounting surface	...	3 mm	...
Standards	...	...	IEEE 802.11 b/g/n, IEEE 802.11 a/n/ac, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab ITU G.993.2, ITU-T G.993.5 (G.vector), ITU-T G.998.4 (G.INP), Full-rate ANSI T1.413 Issue 2, ITU-T G.992.1(G.DMT), ITU-T G.992.2(G.Lite), ITU-T G.994.1 (G.hs), ITU-T G.995.1, ITU-T G.992.3 (G.DMT.bis), ITU-T G.992.4 (G.lite.bis), ITU-T G.992.5
LAN ports	...	...	• 1 x 10/100 Mbps - LAN/WAN, • 3 x 10/100 Mbps - LAN
Resolution	2960 x 1668 - 5 Mpx , 2880 x 1620 - 4.7 Mpx , 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2048 x 1536 - 3 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p	...	...
Lens	2.8 ... 13.5 mm - Motozoom	...	...
LED indicators	...	...	Power, DSL, INTERNET, WLAN, LAN
View angle	113 ° ... 36 ° (manufacturer data)	...	...
WAN interface	...	...	• 1 x RJ-11, ADSL / ADSL2 / ADSL2+ / VDSL / VDSL2 • 1 x RJ-45
Range of IR illumination	40 m	...	...
White light LED illuminator range	50 m	...	...
Transmitter power	...	...	< 20 dBm @ 2.4 GHz , < 23 dBm @ 5 GHz
Min. illumination	0.003 Lux / F1.0 (color)	...	...
S/N ratio	> 56 dB	...	...
Baud rates	...	...	300 Mbps @ 2.4 GHz + 867 Mbps @ 5 GHz

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

RS-485 interface	—	...	...
DHCP server	...	...	✓
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...	...
Firmware update	...	...	✓
DDNS	...	...	• DynDNS • No-IP
Image compression method	AI H.265 / H.265+ / AI H.264 / H.264+	...	...
Alarm inputs / outputs	1 / 1	...	...
Operation modes	...	...	ADSL/VDSL modem, Router, Access Point, Bridge WDS
Audio	<ul style="list-style-type: none"> <li>• Microphone built-in - 2 pcs,</li> <li>• External microphone input,</li> <li>• Speaker built-in</li> <li>• Audio output</li> <li>• Bi-directional audio streaming support</li> <li>• Audio detection</li> </ul>	...	...
Main stream frame rate	20 fps @ 5 Mpx 25 fps @ 4 Mpx	...	...
Protections	...	...	<ul style="list-style-type: none"> <li>• LAN : NAT, SPI network firewall, Access control, IP-MAC Binding, Support DoS defence, parental control</li> <li>• WLAN : WEP 64/128-bit, WPA/WPA2, WPA-PSK/WPA2-PSK, QSS (Quick Secure Setup) - WPS</li> </ul>
Network interface	10/100 Base-T (RJ-45)	...	...
Management interface	...	...	Web browser, TP-LINK Tether
Network protocols	IPv4/IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, SAMBA, PPPoE, SNMP	...	...
WEB Server	Built-in	...	...
Max. number of on-line users	20	...	...
ONVIF	21.12	...	...
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">DMSS</a></li> <li>• iOS (iPhone): Free application <a href="#">DMSS</a></li> </ul>	...	...
Default IP address	192.168.1.108	...	...



Main features	...	...	<ul style="list-style-type: none"> <li>• Enable/disable wireless network</li> <li>• SSID hiding</li> <li>• QoS</li> <li>• WMM (Wi-Fi Multimedia),</li> <li>• Rate limit</li> <li>• Internet access filtering</li> <li>• Wireless transmission statistics</li> <li>• Firewall</li> <li>• Remote management</li> <li>• DHCP : DHCP server, DHCP client list</li> <li>• Port forwarding : Virtual Server, Port Triggering, DMZ, ALG, UPnP</li> <li>• VPN networks: IPsec VPN, L2TP VPN, PPTP VPN, VPN Pass-through</li> <li>• IPv6 compliance</li> <li>• Static / dynamic routing</li> <li>• Port Mapping</li> <li>• IGMP Snooping V1/V2/V3</li> <li>• Guest Network - a separate and secure network for guests</li> <li>• Built-in 4-port switch</li> <li>• ON/OFF button</li> <li>• WPS button</li> <li>• The WPS function allows to easy establish an encrypted connection</li> <li>• RESET button</li> <li>• The DSL line splitter included</li> </ul>
Default admin user / password	admin / - The administrator password should be set at the first start	...	...
Web browser access ports	80, 37777	...	...
PC client access ports	37777	...	...
Operation temp	...	...	0 °C ... 40 °C
Mobile client access ports	37777	...	...
Port ONVIF	80	...	...
Permissible relative humidity	...	...	10 % ... 90 %
RTSP URL	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...	...



Main features	<ul style="list-style-type: none"> <li>• Active deterrence function, Alternately flashing LEDs: red and blue - frequency configuration, Siren sound - 3 volume levels</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• Quick Pick - AI technology enabling, together with the recorder, quick identification of interesting objects (people/vehicles) based on an artificial intelligence algorithm. It allows to extract and compare the colors of clothes and vehicles</li> <li>• SMD 4.0 - searching for an object classified as: human, motor vehicle - increased detection distance and resistance to false alarms</li> <li>• AI SSA AI Smart Scene Adaptive - scene auto-adaptation using deep learning algorithms to detect environmental conditions such as rain, fog, backlight, low light and flickering, in order to set the optimal image parameters</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Day/night mode</li> <li>• Full Color - colorful night mode</li> <li>• Auto White Balance</li> <li>• AGC - Automatic Gain Control</li> <li>• Motion Detection - max. 4 zones</li> <li>• Privacy zones - max. 8</li> <li>• Mirror - Mirror image</li> <li>• Light and sound alarm</li> <li>• White light (LED) illuminator built-in : 2 LEDs</li> <li>• IVS analysis : crossing the line (tripwire), intrusion - classification of people and vehicles, scene changing, video tampering, Audio detection</li> </ul>	...	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 570 mA</li> </ul>	...	12 V DC / 1 A (power adapter included)
Power consumption	<ul style="list-style-type: none"> <li>max. 8.2 W @ PoE</li> <li>max. 6.8 W @ 12 V</li> </ul>	...	...
Housing	Compact - Metal	...	...
Color	White + Black	Black	...
"Index of Protection"	IP67	...	...
Vandal-proof	—	...	...
Operation temp	-30 °C ... 60 °C	...	...
Weight	1.05 kg	1.33 kg	0.31 kg
Dimensions	289 x 95 x 85 mm	300 x 250 x 38 mm	257 x 160 x 37 mm
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Russian, Portuguese, Romanian, Ukrainian, Hungarian, Italian	...	...
Manufacturer / Brand	DAHUA	...	TP-LINK
Guarantee	3 years	2 years	2 years