



	EXTENSION CORD WITH GROUNDING PS-3X1.0-3M/W 3 m	ACCESS CONTROLLER MC16-PAC-ST-3-KIT ROGER
		
	6.97 CHF 6.97 CHF	642.43 CHF 642.43 CHF
Length of the cable	3 m	...
Wire gauge	3 x 1 mm ²	...
Number of served transitions	...	3 (two-way)
Number of supported readers	...	12
Rated voltage	230 V AC / 50 Hz	...
Total maximal current	10 A	...
Number of users	...	unlimited (purchase of the appropriate license required)
Maximal total load	2300 W	...
Number of outlets	1 x CEE 7/5	...
Number of media per ID	...	8 - Proximity card, PIN code, fingerprint, etc.
Fuse	—	...
Buffer memory	...	8 000 000 events buffer
Switch	—	...
Number of access zones	...	6
Color	White	...
Number of alarm zones	...	6
Battery backup support	...	12 V / 20 Ah
Communication	...	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RACS 5 v2 (Roger) • RS-485 interface

Main features	...	<ul style="list-style-type: none"> • Metal housing • The MCX4D I/O expander included • Integrated support in VISO ST software • Functions in the VISO ST system: <ul style="list-style-type: none"> - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system : 128
Power supply	...	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC
Operation temp	...	5 °C ... 40 °C
Permissible relative humidity	...	10 % ... 95 % (non-condensing)
Weight	0.26 kg	4.08 kg
Dimensions	...	405 x 365 x 120 mm
Manufacturer / Brand	...	ROGER
Guarantee	2 years	3 years