



	SOFT START MODULE SF-1	OBJECT PROTECTION SYSTEM MANAGEMENT SERVER IVSS7008-1I DAHUA
		
	7.36 EUR 7.36 EUR	4796.19 EUR 4796.19 EUR
Standard	...	TCP/IP
Number of control inputs	1	...
Number of power inputs	1	...
Number of power outputs	1	...
Supported resolutions	...	max. 12 Mpx - 4000 x 3000 px
Voltage	230 V AC	...
Number of video channels	...	max. 128
Maximal output power	1150 W	...
Protection type	5 A 5/20mm delayed fuse	...
Video outputs	...	<ul style="list-style-type: none"> • 3 pcs HDMI 4K • 2 pcs VGA
Audio inputs	...	1 pcs Microphone - Cinch socket
Connectors type	3 x screw terminals max. 1.5 mm ²	...
Montage hole diameter	3 mm	...
Audio outputs	...	2 pcs - Cinch socket
Mounting holes distance	52 x 47 mm	...
Supported hard drives	...	8 x 10 TB SATA III + eSATA , Possibility of operation the disks in RAID 0/1/5/6/10 array
Searching and playback the records	...	Records searching: by time and events type. Records playback: forward, backward, fast, slow "Frame by Frame" playback function Records playback from max. 36 channels in the same time - local access Records playback from max. 16 channels in the same time - remote access
Network interface	...	4 x 10/100/1000 Base-T

Bitrate	...	max. 400 Mbps (incoming data) max. 320 Mbps (recording) max. 96 Mbps (outgoing data)
Network functions	...	Full support via network, Remote records copying, Web-Server built-in
Mobile phones support	...	✓
Default IP address	...	192.168.1.108
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80, 37777
PC client access ports	...	37777
Alarm inputs / outputs	...	16 / 8
PTZ control	...	IP Speed Dome Cameras, RS-485
RS-485	...	✓
RS-232	...	✓
USB	...	2 x USB 2.0 2 x USB 3.0
Motion Detection	...	✓
Intelligent image analysis	...	✓
Mouse support	...	✓
ANPR	...	max. 32 cameras
Face recognition	...	max. 20 cameras

Main features	...	<ul style="list-style-type: none"> • Cooperation with DAHUA recorders • IP Dahua cameras support • Automatic search for cooperating devices in the local network • Support for devices with the ANPR vehicle identification functions and face recognition • Recognizing and searching on recordings of people on the basis of data including information about: the vehicle the person is moving, license plates, clothing and face recognition • Cooperation with the wall of monitors • Cooperation with the controllers of the NKB series • Integration with the alarm system : <ul style="list-style-type: none"> - Signaling of events registered on the server by alarm outputs - Setting the system arming schedules - Calling up the action after receiving the signal from the alarm control panel - Transmission of information about the triggered alarm to selected users • Intelligent image analysis : Intelligent Object Tracking, people counting, heat map • The possibility of redundant work
Power supply	...	100 ... 240 V AC
Weight	0.04 kg	8.55 kg
Dimensions	60 x 55 x 28 mm	482 x 446 x 91 mm - RACK 19", 2U
Supported languages	...	English
Country of origin	...	China
Manufacturer / Brand	...	DAHUA
Guarantee	2 years	5 years