

	<a href="#">IP CAMERA IPC-HDW2549TM-S-IL-0280B-BLACK WizSense - 5 Mpx 2.8 mm DAHUA</a>	<a href="#">POWER DISTRIBUTION UNIT ACAR-S8/FA/RACK</a>	<a href="#">ACCESS CONTROL PANEL ACCO-NT2.SATEL</a>
			
	2107.27 DKK 2107.27 DKK	221.98 DKK 221.98 DKK	2822.98 DKK 2822.98 DKK
Standard	TCP/IP	...	...
Sensor	1/2.7 " Progressive Scan CMOS	...	...
Rated voltage	...	230 V AC / 50 Hz	...
Matrix size	5 Mpx	...	...
Nominal load current	...	10 A (total)	...
Inputs	...	...	• 8 pcs - Mainboard inputs • max. 264
Nominal voltage of surge suppressor	...	250 V / 50 Hz	...
Protection level of surge suppressor	...	≤ 1.3 kV (L/N)	...
Number of outlets	...	8 grounded outlets 10A/250V	...
Automatic delayed fuse	...	✓	...
Outputs	...	...	• 8 pcs - Mainboard inputs • max. 264
Nominal stroke current	...	2 kA (L/N) - 8/20 μs	...
Communication	...	...	• 2 x RS-485 • Expander bus - up to 32 expander modules
Maximum stroke current	...	6.5 kA (L/N) - 8/20 μs	...
Leak current	...	< 0.5 mA	...
Response time	...	< 25 ns	...
Switch	...	two-way, with light indication	...
Events memory	...	...	• Events saving to the micro SD card (included) • Recording up to 1 000 000 events from the control panel, • Max. 100 000 events read from each access control module
Length of the cable	...	2.9 m	...
Users + admins	...	...	• 8000 + 1 • Max. 65 000 users in the whole ACCO NET system
Resolution	2960 x 1668 - 5 Mpx , 2880 x 1620 - 4.6 Mpx , 2688 x 1520 - 4 Mpx , 2048 x 1536 - 3 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p	...	...
Lens	2.8 mm	...	...
Output load	...	...	• OC : 50 mA / 12 V DC • +EX : 0.5 A / 12 V DC • AUX : 0.5 A / 12 V DC
View angle	• 111 ° (manufacturer data) • 104 ° (our tests result)	...	...
White light LED illuminator range	30 m	...	...
Range of IR illumination	30 m	...	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...	...
Main features	...	...	<ul style="list-style-type: none"> <li>• Support for up to 255 access control modules</li> <li>• Ability to create up to 255 partitions in 1 control panel (up to 255 access control modules can be defined in one partition)</li> <li>• Ability to add up to 16 passageways (up to 16 partitions can be defined in each passageway)</li> <li>• Ability to block/unblock partition at a specified time, or as per access schedule,</li> <li>• Ability to assign 4 identifiers and a keyfob to a single user,</li> <li>• Ability to assign up to 4 proximity cards / DALLAS chips (iButtons) to a user,</li> <li>• Up to 256 access calendars, weekly schedules, daily schedules, time frames</li> <li>• Ability to control the control panel outputs by using keyfobs</li> <li>• Implementation of logic functions on inputs and outputs</li> <li>• Support for turnstiles</li> <li>• Electrical protection of all inputs and outputs as well as communication buses</li> </ul>
Main stream frame rate	<ul style="list-style-type: none"> <li>• 20 fps @ 5 Mpx</li> <li>• 25 fps @ 4 Mpx</li> </ul>	...	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...	...
RS-485 interface	—	...	...
Battery backup support	...	...	—
Alarm inputs / outputs	—	...	...
Operation temp	...	...	-10 °C ... 55 °C
Permissible relative humidity	...	...	93 % (non-condensing)
Audio	<ul style="list-style-type: none"> <li>• Microphone built-in</li> <li>• Audio transmission via network</li> <li>• Audio detection</li> <li>• Compliance with the AAC standard</li> </ul>	...	...
Network interface	10/100 Base-T (RJ-45)	...	...
Network protocols	IPv4/IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, PPPoE, Bonjour	...	...
WEB Server	Built-in	...	...
Max. number of on-line users	20	...	...
ONVIF	21.12	...	...
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">DMSS</a></li> <li>• iOS (iPhone): Free application <a href="#">DMSS</a></li> </ul>	...	...
Default IP address	192.168.1.108	...	...
Default admin user / password	admin / - The administrator password should be set at the first start	...	...
Web browser access ports	80, 37777	...	...
PC client access ports	37777	...	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Mobile client access ports	37777	...	...
Port ONVIF	80	...	...
RTSP URL	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...	...
Main features	<ul style="list-style-type: none"> <li>• Smart Dual Illumination technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• NAS - Network Attached Storage support</li> <li>• Day/Night mode (color/b&amp;w/auto)</li> <li>• ICR - Movable InfraRed filter</li> <li>• Auto White Balance</li> <li>• AGC - Automatic Gain Control</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Configurable Privacy Zones</li> <li>• video tampering</li> <li>• Mirror - Mirror image</li> <li>• Full Color - colorful night mode</li> <li>• Smart motion detection (with recognizing people and vehicles)</li> <li>• SMD PLUS - searching for an object classified as: human, motor vehicle</li> <li>• IVS analysis : intrusion, crossing the line (tripwire) - classification of people and vehicles</li> </ul>	...	...
Housing	Dome - Metal + Plastic	RACK 19", 1U, Plastic - non-flammable	...
Color	Black	...	...
"Index of Protection"	IP67	...	...
Vandal-proof	—	...	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 380 mA</li> </ul>	...	12 V DC / 140 mA (max)
Power consumption	<ul style="list-style-type: none"> <li>• ≤ 5.4 W @ PoE</li> <li>• ≤ 4.6 W @ 12 V DC</li> </ul>	...	...
Operation temp	-40 °C ... 60 °C	...	...
Weight	0.48 kg	0.61 kg	0.096 kg
Dimensions	Ø 122 x 99 mm	445 x 54 x 55 mm	151 x 69 x 17 mm
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Russian, Portuguese, Romanian, Turkish, Ukrainian, Hungarian, Italian	...	...
Manufacturer / Brand	DAHUA	...	SATEL
Guarantee	3 years	2 years	2 years