

	COVER PLATE A19-MASK	SWITCH POE CS4006-4ET-60 4-PORT DAHUA
		
	56.13 CZK 56.13 CZK	2688.11 CZK 2688.11 CZK
Color	Black	...
LAN ports	...	<ul style="list-style-type: none"> • 4 x RJ45 10/100 Base-T (1 x Hi-PoE + 3 x PoE (802.3af/at)), • 2 x RJ45 10/100/1000 Base-T - Uplink
Transmission speed	...	<ul style="list-style-type: none"> • 10 / 100 Mbps : 4 LAN & PoE ports, • 10 / 100 / 1000 Mbps : 2 Uplink ports
Maximal output power	...	<ul style="list-style-type: none"> • 60 W / port Hi-PoE - Port 1 • 30 W / port PoE 802.3af/at - 2 ... 4 ports
Maximal total power	...	60 W
MAC addresses table	...	8k
Management	...	✓
Operation modes	...	Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6
LED diodes	...	Power, System, PoE, Link/Act

Main features	...	<ul style="list-style-type: none"> • Switch is managed through the web and the cloud (DoLynk Care application) • PoE power mode : The device supports 8-pin power supply - wires : 1-2(+), 3-6(-), 4-5(+), 7-8(-) • Intelligent management of Power Supply Unit power's output stage • protection against lightning discharges and voltage differences and strokes between devices • Watchdog PoE • Loop Protection • Compliance with the LLDP protocol • Port Based VLAN : 32 • Data Flow Control (802.3x) • DHCP client • RESET button • Kensington Lock • Possibility to mount to the wall
Certificates	...	CE
Protections	...	<ul style="list-style-type: none"> • Protection against lightning discharges (common/differential) : 4 / 2 kV • Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV
Housing	...	Desktop, Metal
Power supply	...	53 V DC / 1.22 A (power adapter included)
Power consumption	...	max. 65 W
Operation temp	...	-10 °C ... 55 °C
Weight	0.19 kg	0.29 kg
Dimensions	218 x 39 x 2 mm	130 x 85 x 26 mm
Manufacturer / Brand	DELTA	DAHUA
Guarantee	3 years	3 years