



	<a href="#">LED LIGHTING CONTROLLER LED-RGBW-WC/RF2 2.4 GHz, RGBW 12 ... 24 V DC MiBOXER / Mi-Light</a>	<a href="#">REMOTE CONTROL FOR LED LIGHTING CONTROLLERS LED-CONTROL/RF2 2.4 GHz, MONO, CCT, RGB, RGBW MiBOXER / Mi-Light</a>
		
	10.80 EUR 10.80 EUR	13.08 EUR 13.08 EUR
Application	Works with LED lighting - (RGBW) 12-24V LED strips	Works with LED lighting : (RGB/RGBW/CCT/MONO) 12-24V LED strips
Number of channels	...	4
Rated voltage	12 ... 24 V DC	...
Power supply	...	2 x 1.5V, type AAA/LR03 battery (not included)
Maximal total load	<ul style="list-style-type: none"> <li>• 144 W @ 12 V,</li> <li>• 288 W @ 24 V</li> </ul>	...
Total maximal current	6 A / Channel, 12 A (total)	...
Number of inputs	1	...
Number of outputs	4 (power)	...
Connector type	<ul style="list-style-type: none"> <li>• screw terminals,</li> <li>• 5.5/2.1 socket / screw terminals - power input</li> </ul>	...
Wireless	2.4 GHz	2.4 GHz
Radio communication range (at open area)	30 m	30 m
Mobile phones support	—	...
Main features	The repeater function allows you to transfer control to subsequent LED-W-WC / LED-RGB-WC / LED-RGBW-WC modules even beyond the direct range of the remote control	Touch control keys
Housing	Plastic	Plastic
Color	White	White
Operation temp	-10 °C ... 40 °C	-20 °C ... 60 °C
Weight	0.03 kg	0.05 kg (without battery)
Dimensions	75 x 36 x 17 mm	120 x 53 x 21 mm
Manufacturer / Brand	MiBOXER / Mi-Light	MiBOXER / Mi-Light
Guarantee	2 years	2 years