

	ALLEN SCREW SL. MBX30/KL-8.8	IP CAMERA BCS-DMIP2300IR-M-III 3.0 Mpx 2.7 ... 12 mm - MOTOZOOM	TV OR MONITOR MOUNT AX-HAMMER	MONITOR CEILING MOUNT MC-504B MACLEAN	ACCESS POINT + ROUTER RG-M18 Wi-Fi 6, 2.4 GHz, 5 GHz, 347 Mbps + 1201 Mbps REYEE	EXTENDER HDMI+USB- EX-70-4KV2	LABEL REMOVER ADHESIVE-REMOVER200ML SPRAY 200 ml TESA
							
	0.21 EUR 0.21 EUR	195.28 EUR 195.28 EUR	27.74 EUR 27.74 EUR	23.36 EUR 23.36 EUR	120.56 EUR 120.56 EUR	178.15 EUR 178.15 EUR	7.87 EUR 7.87 EUR
Standard	...	TCP/IP
Size	M8
Package	Spray 200 ml
Sensor	...	1/3" Progressive Scan CMOS
Material	Steel galvanized
Supported HDMI resolutions	max. 4K UHD @ 60 Hz	...
Application	Removal of self-adhesive labels
Strength class	8.8
Matrix size	...	3.0 Mpx
Frequency range	• 2.4 GHz, • 5 GHz
Wrench size	6 mm
Mounting standard	VESA 75, 100, 200, 200 x 100, 300, 400 x 200, 400, 600 x 400	VESA 75, 100, 100 x 200, 200
Thread length	30 mm
Screen size range	23" ... 70"	23" ... 42"
Bearing capacity	50 kg	30 kg
Resolution	...	2048 x 1536 - 3 Mpx, 1920 x 1080 - 1080p, 1280 x 720 - 720p
Antenna type	2x2 MU-MIMO - built-in • 4 dBi @ 2.4 GHz - 2 pcs • 6.8 dBi @ 5 GHz - 2 pcs
Distance from mounting surface	83 ... 455 mm
Standards	IEEE 802.11ax Wi-Fi 6
Tilt adjustment	0° ... 15°	-20° ... 20°
Maximal transmission range	• 60 m - UTP cat. 6, 6A, 7 @ 4K UHD (manufacturer data) • 70 m - UTP cat. 5e @ 1080p (our tests result) • 20 m - UTP cat. 5e @ 4K UHD (our tests result) • 60 m - UTP cat. 6 @ 4K UHD (our tests result)	...
Horizontal rotation	45° ... 45°	90°
Baud rates	547 Mbps @ 2.4 GHz + 1201 Mbps @ 5 GHz
Rotation in the plane of the screen	—	—
LAN ports	2 x 10 / 100 / 1000 Mbps - RJ45
WAN interface	1 x 10 / 100 / 1000 Mbps - RJ45
Lens	...	2.7 ... 12 mm - Motozoom
Port USB	—
View angle	...	87° ... 29° (manufacturer data)
LED indicators	Power / System / Mesh, Signal indicator
DDNS	—
DHCP server	✓
S/N ratio	...	> 50 dB
Firmware update	✓
Range of IR illumination	...	60 m
RS-485 interface	...	—
Memory card slot	...	Micro SD memory cards up to 128GB support (possible local recording)
Image compression method	...	H.264 / MJPEG
Protections	• WPA/WPA2 • Black list • parental control • SSID hiding • Firewall
Alarm inputs / outputs	...	—
Audio	...	—
Operation modes	• Repeater • Router • Access Point • WISP
Management interface	• Configuration using the Ruijie Reeye application • Remote management • Web browser
Bitrate	...	• 40 ... 10240 kbps @ H.264 • 40 ... 24576 kbps @ MJPEG
Network interface	...	10/100 Base-T (RJ-45)
Transmitter power	max. 20 dBm @ 2.4 GHz max. 27 dBm @ 5 GHz
Network protocols	...	HTTP, HTTPS, TCP, ARP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, IPv4/IPv6, QoS, UPnP, NTP, Bonjour, IEEE 802.1x, Multicast, ICMP, IGMP, SNMP
WEB Server	...	Built-in, Web Viewer

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	DIN 912 compliance	<ul style="list-style-type: none"> • Wi-Fi 6 support - a standard that offers higher speeds, better performance in high-traffic environments • OFDMA • Beamforming (TxBF) - technology that allows to create a beam of radio waves in order to improve the quality of connection with client devices located further away from the signal source • MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network • Load balance • WLAN : max. 6 x BSSID • IPv4/IPv6 - Static routing • PPPoE • IPTV • WMM support (QoS mechanism of the 802.11e standard) • VPN support : PPTP VPN Server / Client • Guest Network - a separate and secure network for guests • Support for Reyee Mesh technology • System logs • RESET button • MESH button 	<ul style="list-style-type: none"> • Very good image quality with no visible distortions caused by compression. • No delays in video transmission. • No delays in mouse control operations • Designed to continuous operation 24/7 	...
Max. number of on-line users	...	10
ONVIF	...	2.42
Power supply PoE
Main stream frame rate	...	25 fps @ 3.0 Mpx
Operation temp	-10 °C ... 45 °C	-20 °C ... 60 °C	...
Permissible relative humidity	5 % ... 95 % (non-condensing)	0 % ... 90 % (non-condensing)	...
Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS ; Android: Free application IMOU • iOS (iPhone): Free application DMSS ; iOS (iPhone): Free application IMOU	Android: Free application Ruijie Reyee iOS (iPhone): Free application Ruijie Reyee
Default IP address	...	192.168.1.108	192.168.110.1
Default admin user / password	...	admin / admin
Web browser access ports	...	80, 37777
PC client access ports	...	37777
Mobile client access ports	...	37777
Port ONVIF	...	80
RTSP URL	...	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Main features	...	<ul style="list-style-type: none"> • Motozoom lens - Controlling from browser, NVR or software • ICR - Movable InfraRed filter • 3D-DNR - Digital Noise Reduction • WDR - Wide Dynamic Range • BLC - configurable Back Light Compensation • HLC - High Light Compensation (spot) • D-ZOOM - Digital Zoom • Day/Night mode (color/b&w/auto) • Configurable Privacy Zones • ROI - improve the quality of selected parts of image 	<ul style="list-style-type: none"> • Extender also allows to extend an USB 2.0 port, eg. in order to control the recorder using the mouse • Support KVM function. • HDR10 support • Transition of the HDMI signal in the transmitter • EDID support • ESD protection 	...	
Power supply	...	• PoE (802.3af), • 12 V DC / 730 mA	12 V DC / 1.5 A (included)	5 V DC / 1 A - 2 pcs (included)	...
Power consumption	...	≤ 8.8 W	max. 18 W
Housing	...	Dome - Metal	Plastic
Color	...	White	Black	Black
"Index of Protection"	...	IP66
Vandal-proof
Operation temp	...	-30 °C ... 60 °C
Weight	0.016 kg	0.580 kg	4.8 kg	2.09 kg	0.36 kg	0.12 kg	0.200 kg
Dimensions	Ø 12.8 x 38.3 mm	Ø 122 x 105 mm	670 x 430 x (83 ... 455) mm	max. 958 x 220 x 218 mm	91 x 91 x 181 mm	85 x 75 x 20 mm - Transmitter or receiver dimensions	Ø 53 x 173 mm
Supported languages	...	English, Polish
Manufacturer / Brand	...	BCS	...	MACLEAN	RUIJIE / REVEE	...	TESA
Guarantee	2 years	2 years	2 years	2 years	3 years	2 years	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00