




	AHD, HD-CVI, HD-TVI, CVBS CAMERA DS-2CE79H0T-IT3ZF(2.7-13.5mm)(C) - 5 Mpx Hikvision	END CLAMP PV-KK/30-50/B FOR SOLAR PANELS 30 mm	BATTERY 12V/5AH-MWS
			
	125.55 EUR 125.55 EUR	0.68 EUR 0.68 EUR	9.47 EUR 9.47 EUR
Material	...	Aluminum	...
Battery capacity	5.0 Ah
Height	...	30 mm	...
Rated voltage	12 V
Hole diameter	...	9 mm	...
Battery charging current	max. 1.5 A
mounting screw	...	—	...
Battery type	Maintenance-free AGM (Absorbent Glass Mat) battery
Standard	AHD, HD-CVI, HD-TVI, CVBS
Connector	T1 type
Sensor	Progressive Scan CMOS
Matrix size	5 Mpx
Battery lifetime	3 ... 5 years
Resolution	2560 x 1944 - 5 Mpx @ AHD / HD-TVI, 20 fps , 2560 x 1440 - 4 Mpx @ AHD / HD-TVI / HD-CVI @ 25 fps , 1920 x 1080 - 1080p @ HD-TVI, 25 fps 960 x 576 - 960H @ CVBS
Range of IR illumination	40 m
IR illuminator power adjustment	Automatic
Lens	2.7 ... 13.5 mm - Motozoom
View angle	• 95 ° ... 26 ° (manufacturer data) • 93 ... 25 (our tests result)
Video output	1 x AHD / HD-CVI / HD-TVI / CVBS - 1 Vpp / 75 Ω, BNC socket

Main features	<ul style="list-style-type: none"> • Motozoom lens • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • BLC - Back Light Compensation • AGC - Automatic Gain Control • ICR - Movable InfraRed filter • Mirror - Mirror image • Sharpness - sharper image outlines
OSD menu	✓
Power supply	12 V DC / 520 mA
Power consumption	≤ 6.2 W
Housing	Dome, Metal
Color	White	Black	...
"Index of Protection"	IP67
Operation temp	-40 °C ... 60 °C
Weight	0.6 kg	0.22 kg	1.36 kg
Dimensions	134 x 124 x 110 mm	50 33 27 mm	90 x 107 x 70 mm
Supported languages	English
Manufacturer / Brand	Hikvision
SAP Code	300615088
Guarantee	3 years	2 years	2 years