



	ACCESS POINT 4G+ LTE Cat. 6 +ROUTER LTE-CA2-103 Wi-Fi 2.4 GHz, 5 GHz, 866 Mbps + 300 Mbps	MODEM 4G LTE, MOBILE ROUTER TL-M7200 Wi-Fi 300Mb/s TP-LINK
		
	108.67 EUR 108.67 EUR	70.70 EUR 70.70 EUR
Frequency range	<ul style="list-style-type: none"> • Wi-Fi : 2.4 GHz, 5 GHz, • LTE : 2600 MHz, 2500 MHz, 2300 MHz, 2100 MHz, 1800 MHz, 900 MHz, 850 MHz, 800 MHz, 700 MHz 	2.4 GHz
Antenna type	<ul style="list-style-type: none"> • 4 x Omnidirectional antenna Wi-Fi, Integrated, • 2 x Omnidirectional antenna 4G LTE, Integrated 	1 x WiFi - Internal antenna , 1 x 4G LTE - Internal antenna
Standards	IEEE 802.11 b/g/n/ac	IEEE 802.11 b/g/n, 4G LTE, 3G DC-HSPA+/HSPA+/HSPA/UMTS
Baud rates	<ul style="list-style-type: none"> • Wi-Fi : 866 Mbps + 300 Mbps, • LTE Cat. 6 : 300 Mbps / 50 Mbps 	<ul style="list-style-type: none"> • LTE : 150 / 50 Mbps, • 11n : 300 Mbps, • 11g : 54 Mbps, • 11b : 11 Mbps
Network type	...	<ul style="list-style-type: none"> • 4G : FDD-LTE B1/B3/B7/B8/B20 - 2100 / 1800 / 2600 / 900 / 800 MHz • 4G : TDD-LTE B38/B40/B41 - 2600 / 2300 / 2500 MHz • 3G : DC-HSPA+/HSPA+/HSPA/UMTS B1/B8 - 2100 / 900 MHz
LAN ports	1 x 10/100/1000 Mbps - Uplink / LAN 4 x 10/100/1000 Mbps - LAN	—
LED indicators	Power, SYS, LTE, Wi-Fi, 4 x Ethernet, WAN	...
SIM socket	1 x mini SIM	...
Ports	...	<ul style="list-style-type: none"> • 1 x micro USB - Battery charging • 1 x SIM socket
DDNS	✓	...
DHCP server	✓	...
Firmware update	✓	...

Protections	WEP, WPA/WPA2, WPA-PSK/WPA2-PSK	...
Management interface	Web browser	...
Receiver sensitivity	...	<ul style="list-style-type: none"> • 11b 11 Mbps : -87.5 dBm • 11g 54 Mbps : -74 dBm • 11n HT20 MCS7 : -70 dBm • 11n HT40 MCS7 : -68 dBm
Transmitter power	< 20 dBm	< 20 dBm
Main features	<ul style="list-style-type: none"> • Built-in 5-port switch • RESET button • Remote management 	<ul style="list-style-type: none"> • ON/OFF button • RESET button • LED diodes : WiFi, INTERNET, Battery • Transmission encryption : WPA-PSK/WPA2-PSK • MAC addresses filtering • SSID hiding • DHCP server • DHCP client list • Max. number of supported devices : 10 • Backup time max. 8 h • Remote management - tpMiFi application • System requirements : Windows XP/Vista/7/8/10, Mac OS, Android, iOS (iPhone, iPad), Windows Phone
Power supply	12 V DC / 1 A (power adapter included)	<ul style="list-style-type: none"> • 2000 mAh Battery • 5 V DC / 1 A Charging via USB port
Operation temp	...	0 °C ... 35 °C
Permissible relative humidity	...	10 % ... 90 % (non-condensing)
Weight	0.42 kg	0.09 kg
Dimensions	238 x 149 x 33 mm	94 x 57 x 20 mm
Manufacturer / Brand	...	TP-LINK
Guarantee	2 years	3 years