



	<a href="#">ACCESS CONTROLLER WITH TEMPERATURE MEASUREMENT ASI7213X-T1 - 1080p DAHUA</a>	<a href="#">IP SPEED DOME CAMERA OUTDOOR TC-H344S SPEC:25X/I/E+/A/V3.0 - 3.7 Mpx 4.8 ... 120 mm TIANDY</a>
		
	2948.64 GBP 2948.64 GBP	828.00 GBP 828.00 GBP
Sensor	1/2.8 " CMOS	1/2.7 " Progressive Scan CMOS
Matrix size	2.1 Mpx 120 x 90 px	...
Resolution	1920 x 1080 - 1080p 120 x 90 px	2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens	...	4.8 ... 120 mm
Standard	TCP/IP	IP
View angle	50 °	58 ° ... 2.8 °
Optical zoom	—	x 25
White light LED illuminator range	5 m	...
Temperature measurement	✓	...
Digital zoom	...	x 16
Range of IR illumination	5 m	150 m
Temperature measurement range	30 °C ... 50 °C	...
Accuracy of temperature measurement	± 0.1 °C	...
Preset rotation speed	...	• 240 °/s (horizontal) • 180 °/s (vertical)
Face recognition distance	0.3 m ... 1.8 m (max 100 000 faces in the database)	...
RFID proximity reader built-in	13.56 MHz S50	...
Internal memory	Support storage of 300 000 records	...
Video output	—	—
Rotation speed (manual control)	...	• 0.1 °/s ... 200 °/s (horizontal), • 0.1 °/s ... 120 °/s (vertical)
RS-232 interface	✓	...
Wiegand interface	✓	...

Horizontal rotation range	...	360 ° - continuous
USB	2 x USB 2.0	...
Vertical rotation range	...	-16 ° ... 90 °
RS-485 interface	✓	✓
Number of presets	...	500
Horizontal scan	...	✓
Route settings	...	8
Image compression method	...	S+265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	2 / 2 - Relay outputs	1 / 1
Audio	Speaker built-in	• Audio input • Audio output
Main stream frame rate	...	25 fps @ 3.7
Network protocols	IPv4, RTSP, RTP, TCP, UDP, P2P	...
Network interface	• 1 x 10/100 Base-T (RJ-45) • 1 x 10/100/1000 Base-T (RJ-45)	10/100 Base-T (RJ-45)
WEB Server	Built-in	Built-in
Max. number of on-line users	...	7
ONVIF	✓	✓
Memory card slot	—	Micro SD card support up to 512GB
Mobile phones support	...	Port no.: 3000 or access by a cloud (P2P) • Android: Free application <a href="#">EasyLive Plus</a> • iOS (iPhone): Free application <a href="#">EasyLive Plus</a>
Access from PC	...	Port no.: 3000 or access by a cloud (P2P) - PC: Free application <a href="#">Easy7 Smart Client Express</a>
Default IP address	192.168.1.108	192.168.1.2
Default admin user / password	admin / - The administrator password should be set at the first start	admin / - The administrator password should be set at the first start
Web browser access ports	80, 37777	80, 443, 3000, 3001, 3002, 23002
Mobile client access ports	...	3000, 3001
PC client access ports	37777	3000, 3001
Port ONVIF	...	80

Intelligent image analysis	...	<ul style="list-style-type: none"> <li>• classification of people and vehicles</li> <li>• crossing the line (tripwire)</li> <li>• double crossing the line</li> <li>• intrusion</li> <li>• abandoned/missing object</li> <li>• illegal parking</li> <li>• people counting</li> <li>• detection of people gathering</li> <li>• heat map</li> <li>• detection of loitering in a given area</li> <li>• running</li> <li>• protective helmet detection</li> <li>• detection of persons on duty</li> <li>• face detection</li> <li>• video tampering</li> </ul>
----------------------------	-----	--



Main features	<ul style="list-style-type: none"> <li>• Temperature measurement</li> <li>• Built-in LCD display showing the image from the video camera and the result of temperature measurement - 7 " capacitive touch screen, 1024 x 600 px</li> <li>• Identification modes : PIN, Proximity identifier 13.56 MHz S50, Face recognition, Any combination of the above</li> <li>• Wiegand 34/26</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• LED indication</li> <li>• Buzzer for acoustic signaling of some system events</li> <li>• AGC - Automatic Gain Control</li> <li>• Sharpness - sharper image outlines</li> <li>• Day/Night mode (color/b&amp;w/auto)</li> <li>• RESET button</li> <li>• AI detection : A solution dedicated to measuring temperature. The camera is able to detect increased object temperature</li> </ul>	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Day/night mode</li> <li>• ICR - Movable InfraRed filter</li> <li>• Motion Detection</li> <li>• Image rotation and mirror</li> <li>• Adaptive adjusting of the IR illuminator power to the lens zoom and outdoor light conditions</li> <li>• Intelligent Object Tracking</li> </ul>
Montage hole diameter	37 mm	...
Power supply	12 V DC / 2 A (power adapter included)	<ul style="list-style-type: none"> <li>• PoE (802.3at),</li> <li>• 12 V DC</li> </ul>
Power consumption	≤ 24 W	≤ 19.4 W
Housing	Aluminum + Tempered glass	Speed Dome, Aluminum
Color	Black + Silver	White + Black
Operation temp	<ul style="list-style-type: none"> <li>• -10 °C ... 55 °C - without temperature measurement</li> <li>• 15 °C ... 32 °C - with temperature measurement</li> </ul>	-30 °C ... 65 °C
"Index of Protection"	—	IP66
Vandal-proof	...	—
Weight	2 kg	3 kg
Dimensions	313 x 130 x 59 mm	Ø 161 x 276 mm

Supported languages	English	Polish, English, Albanian, Arabic, Korean, French, Hebrew, Spanish, Dutch, German, Portuguese, Russian, Thai, Turkish, Ukrainian, Vietnamese, Italian
Manufacturer / Brand	DAHUA	TIANDY
Guarantee	3 years	3 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00