




| | | | |
|----------------------------|---|--|--|
| | WHOLE HOME WI-FI SYSTEM DECO-M4(2-PACK) 2.4 GHz, 5 GHz 300 Mbps + 867 Mbps TP-LINK | AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR BCS-L-XVR1604-4KE-IV 16 CHANNELS +eSATA BCS Line | HUB USB 3.0 F7U-U3-CR-BP 1 m |
| |  |  |  |
| | 89.27 EUR 89.27 EUR | 1128.37 EUR 1128.37 EUR | 14.06 EUR 14.06 EUR |
| Number of devices included | 2 pcs | ... | ... |
| Frequency range | 2.4 GHz, 5 GHz | ... | ... |
| Antenna type | 2 x Omnidirectional antenna - embedded | ... | ... |
| Standard | ... | AHD, HD-CVI, HD-TVI, CVBS, TCP/IP | ... |
| Connectors | ... | ... | <ul style="list-style-type: none"> • 1 x Socket - micro USB 3.0 • 7 x socket - USB-A • 1 x Power socket - micro USB |
| Video inputs | ... | 16 pcs BNC | ... |
| Length of the cable | ... | ... | 1 m |
| USB standard | ... | ... | 3.0 |
| Standards | IEEE 802.11 b/g/n @ 2.4 GHz IEEE 802.11 a/n/ac @ 5 GHz | ... | ... |
| Baud rates | 300 Mbps + 867 Mbps | ... | ... |
| Video outputs | ... | 1 pcs HDMI 4K 1 pcs HDMI 1 pcs VGA 1 pcs Composite Video (CVBS) - BNC socket | ... |
| LED indicators | ✓ | ... | ... |
| DDNS | ✓ | ... | ... |
| DHCP server | ✓ | ... | ... |
| Firmware update | Automatic | ... | ... |
| Audio inputs | ... | 4 pcs BNC , 1 pcs BNC - Microphone 16 Channels - Audio support via coaxial cable, HD-CVI only | ... |

| | | | |
|--------------------------|--|---|--|
| Protections | WEP 64/128-bit, WPA/WPA2, WPA-PSK/WPA2-PSK DoS attacks protection, SPI network firewall, domain filtering, IP and MAC filtering, IP and MAC binding | ... | ... |
| Audio outputs | ... | 1 pcs BNC 1 pcs BNC - Microphone | ... |
| LAN ports | 2 x 10/100/1000 Mbps 2 x 10/100/1000 Mbps (RJ-45. UTP/STP) | ... | ... |
| Management interface | Web browser , | ... | ... |
| Image compression method | ... | AI Coding / H.265+ / H.265 / H.264+ / H.264 | ... |
| Transmitter power | max. 20 dBm @ 2.4 GHz max. 23 dBm @ 5 GHz | ... | ... |
| Main features | <ul style="list-style-type: none"> • The DECO-M4(2-PACK) offers a stable connection with speeds up to 1.167 Gb/s and is compatible with all cable modems, and the entire system can support up to 100 wireless devices in the network • TP-Link Mesh technology: MU-MIMO, Automatic route selection, AP control, Bandwidth control, Beamforming • Port forwarding • Router mode / Access Point mode • Compatible with Amazon Alexa, IFTTT • IPv4/IPv6 • Guest Network - a separate and secure network for guests • Black list • Firewall • WMM (Wi-Fi Multimedia) • Internet access filtering • Access control, parental control • Remote management • Static / dynamic routing • Wireless transmission statistics • Compatible with all Deco models | ... | <ul style="list-style-type: none"> • Solid workmanship • It can be used as a charger for multiple devices when connected to an external power source via the micro USB socket • LED indication • Transparent housing |



| | | | |
|---------------------------------|--|--|-----|
| System requirements | • Android 4.3 or newer • iOS 9.0 or newer | ... | ... |
| Operation temp | 0 °C ... 40 °C | ... | ... |
| Permissible relative humidity | 10 % ... 90 % (non-condensing) | ... | ... |
| Image records resolutions | ... | <ul style="list-style-type: none"> • AHD / HD-CVI / HD-TVI : 8 Mpx - 3840 x 2160 , 4K-N - 1920 x 2160 , 6 Mpx - 2880 x 1920 - HD-CVI only , 5 Mpx - 2592 x 1944 , 4 Mpx - 2560 x 1440 , 4M-N - 1280 x 1440 , 3 Mpx - 2048 x 1536 - AHD / HD-TVI only , 1080p - 1920 x 1080 , 720p - 1280 x 720 • CVBS : 960H - 960 x 576 • IP : max. 12 Mpx - 4000 x 3000 | ... |
| Recording speed adjustment | ... | <ul style="list-style-type: none"> 12 Mpx IP @ 1 ... 25 fps 8 Mpx @ 1 ... 7 fps 4K-N @ 1 ... 15 fps 6 Mpx @ 1 ... 10 fps 5 Mpx @ 1 ... 12 fps 4 Mpx @ 1 ... 15 fps 4M-N @ 1 ... 25 fps 3 Mpx @ 1 ... 15 fps 1080p @ 1 ... 25 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps for each channel | ... |
| Operation modes | ... | 16 x AHD / HD-CVI / HD-TVI / CVBS / IP + 16 x IP | ... |
| Recording modes | ... | Manual, Sensor, Motion detection, Schedule | ... |
| Supported hard drives | ... | 4 x 16 TB SATA + 1 x eSATA | ... |
| External storage devices backup | ... | Save single frames and whole records from DVR drive to the USB drive | ... |

| | | | |
|------------------------------------|-----|--|-----|
| Searching and playback the records | ... | Records searching: by time + timeline with record type. Playback: forward, fast, slow, step Advanced searching (to the one second accuracy) All channels synchronous playback, Smart Search function 1/4/9/16 channel synchronous playback | ... |
| Network functions | ... | Full support via network, Remote records copying, Web-Server built-in max. 128 on-line users | ... |
| USB | ... | 1 x USB 2.0 2 x USB 3.0 | ... |
| Mobile phones support | ... | Port no.: 37777 or access by a cloud (P2P) • Android: Free application BCS Manager • iOS (iPhone): Free application BCS Manager | ... |
| Alarm inputs / outputs | ... | 16 / 6 | ... |
| PTZ control | ... | IP Speed Dome Cameras Control compatible with coax PTZ HD-CVI RS-485 - PELCO-D/P | ... |
| Motion Detection | ... | Split the screen into zones : 22 x 18 motion zones | ... |
| Main features | ... | • RS-232 interface • Privacy zones - max. 4 • SMD PLUS - searching for an object classified as: human, motor vehicle, • POS - support the machines installed in the points of sales and displaying the date from them as overlaid text on selected channel window, • Intelligent image analysis : crossing the line (tripwire), intrusion - classification of people and vehicles, face detection | ... |
| Mouse support | ... | ✓ | ... |
| IR remote controller in the set | ... | ✓ | ... |

| | | | |
|----------------------|--|-----------------------------------|---|
| Power supply | 12 V DC / 1.2 A (power adapter included) | 100 V ... 240 V AC | 5 V DC / 3 A (power adapter not included) |
| Power consumption | ... | max. 20 W (without HDD) | ... |
| Color | ... | Black | ... |
| Weight | 0.36 kg | 4.86 kg | 0.050 kg |
| Dimensions | Ø 91 x 190 mm | 440 x 421 x 76 mm, RACK 19", 1.5U | 135 x 35 x 19 mm |
| Supported languages | ... | Polish, English | ... |
| Manufacturer / Brand | TP-LINK | BCS Line | ORICO |
| Guarantee | 3 years | 3 years | 2 years |