



	IP CAMERA IPC3615SB-ADF28KMC-I0 Tri-Guard - 5 Mpx 2.8 mm UNIVIEW	INVERTER POWER GENERATOR F-2001/IS 1800 W FOGO
		
	317.01 EUR 317.01 EUR	670.34 EUR 670.34 EUR
Standard	TCP/IP	...
Nominal power	...	1800 W
Maximum power	...	2000 W
Sensor	1/2.7 " Progressive Scan CMOS	...
Output voltage	...	230 V AC
Matrix size	5 Mpx	...
Number of outlets	...	1 pcs - single-phase
Built-in voltmeter	...	—
Output frequency	...	50 Hz
Voltage stabilization	...	Inverter (provides full voltage stabilization)
12V DC output	...	✓
Engine capacity	...	79.7 cm ³
Resolution	2880 x 1620 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p	...
Engine type	...	Rato R 80 I 1 cylinder, 4 stroke, gasoline, air cooled
Lens	2.8 mm	...
Starting the engine	...	Manual
Noise level during operation	...	89 dB
View angle	• 101 ° (manufacturer data) • 105 ° (our tests result)	...
White light LED illuminator range	30 m	...
Range of IR illumination	30 m	...
Average fuel consumption	...	• 0.67 l/h - 50 % power • 1.1 l/h - 100 % power
S/N ratio	> 56 dB	...
Fuel tank capacity	...	4 l
RS-485 interface	—	...
Fuel gauge	...	✓
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...
Image compression method	Ultra 265 / H.265 / H.264 / MJPEG	...

Alarm inputs / outputs	—	...
Main features	...	<ul style="list-style-type: none"> • Low oil level indicator light • Overload signaling • Overload protection • Battery charging possible • Save fuel by automatically reducing the revs as the load decreases • Possibility to combine two F-2001/IS power generators into one generator set
Audio	<ul style="list-style-type: none"> • Microphone built-in, • Speaker built-in • Audio transmission via network • Audio detection 	...
Main stream frame rate	25 fps @ 5 Mpx	...
Network interface	10/100 Base-TX (RJ-45)	...
WEB Server	Built-in	...
Max. number of on-line users	32	...
ONVIF	✓	...
Mobile phones support	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EZView • iOS (iPhone): Free application EZView 	...
Default IP address	DHCP or 192.168.1.13	...
Default admin user / password	admin / 123456	...
Web browser access ports	80, 554	...
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation	...
Mobile client access ports	80	...
Port ONVIF	80	...
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream	...

Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • Active deterrence function - Light and sound alarm • F-DNR (Defog) - Reduction of image noise caused by precipitation • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • BLC/HLC - Back Light / High Light Compensation • Auto White Balance • ROI - improve the quality of selected parts of image • Possibility to change the resolution, quality and bit rate • Sharpness - sharper image outlines • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • Privacy zones - max. 4 • Motion detection with human/vehicle silhouette recognition • Intelligent image analysis : crossing the line (tripwire), intrusion, entering the marked area, leaving the marked area, people counting, crowd gathering estimation, face detection • Overvoltage protection : 4 kV 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 625 mA 	...
Power consumption	≤ 7.5 W	...
Housing	Dome, Metal	...
Color	White	Red
"Index of Protection"	IP67	...
Vandal-proof	—	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.42 kg	21.1 kg
Dimensions	Ø 110 x 95 mm	498 x 290 x 459 mm
Supported languages	Polish, English, Czech, Spanish, Dutch, French, German, Portuguese, Slovak, Hungarian, Italian	...
Manufacturer / Brand	UNIVIEW	FOGO
Guarantee	3 years	12 months