




	UPS VI-1500/R1U 1500 VA PowerWalker	CABLE MANAGER OKR-24/P	KRONE BACK-MOUNT FRAME LSA-GN-10/5
			
	539.95 EUR 539.95 EUR	7.32 EUR 7.32 EUR	3.75 EUR 3.75 EUR
Nominal power	900 W
Number of mounted profile modules	5 pcs
Color	...	Black	...
Apparent Power	1500 VA
Type of mounted profile modules	10PAR
Material	...	Metal / Plastic	...
Input voltage	165 ... 290 V AC
Input frequency	45 ... 55 Hz
Output voltage	230 V AC (Pure Sine Wave)
Output frequency	50 Hz
Voltage adjustment	± 10 %
Frequency adjustment	—
Transfer time	max. 4 ms
Charging time (recover to 90% capacity)	8 hours
Battery	4 x 6V/9Ah
Estimated battery operation time	<ul style="list-style-type: none"> • 3.1 minutes @ 100% load • 12.1 minutes @ 50% load
Number of outputs	4 pcs IEC320 C13 socket
Management software	PowerMaster
Protections	<ul style="list-style-type: none"> • Fuse • Overvoltage • Overload protection • EPO (Emergency power off) switch
Operation state indication	<ul style="list-style-type: none"> • LCD display: operation mode, battery charging level, in/out voltage level • Sound signaling - with Mute function
Main features	<ul style="list-style-type: none"> • Auto restart while AC is recovering • "Cold Start" function • Expansion slot • Battery charge and maintenance control • USB/RS-232 communication port 	<ul style="list-style-type: none"> • RACK 19", 1U • Number of cable holders : 24 	...

Application	<ul style="list-style-type: none"> • Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment
Housing type	RACK
Operation temp. / Relative humidity	0 °C ... 40 °C / 0 ... 90 % (non-condensing)
Weight	16.31 kg	0.38 kg	...
Dimensions	435 x 400 x 44 mm ; RACK 19", 1U	483 x 44 x 62 mm	112 x 112 x 50 mm
Manufacturer / Brand	PowerWalker
Guarantee	2 years	2 years	2 years

