



	<a href="#">PATCHCORD RJ45/0.2-BLUE 0.2 m</a>	<a href="#">ACCESS POINT 4G LTE +ROUTER RUT901 Dual SIM 2.4 GHz 300 Mbps Teltonika</a>
		
	7.39 NOK 7.39 NOK	1564.51 NOK 1564.51 NOK
Frequency range	...	2.4 GHz
Cable	UTP cat. 5e : RJ-45 - Plug / RJ-45 - Plug	...
Color	Blue	...
Antenna type	...	2 x Omnidirectional antenna Wi-Fi - 5 dBi (SMA connector) , 2 x Omnidirectional antenna 4G LTE - 4 dBi (SMA-RP connector)
Length of the cable	0.2 m	...
Standards	...	IEEE 802.11 b/g/n, 4G, 3G, 2G
Baud rates	...	11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps LTE : 150 / 42 / 0.236 Mbps (4G / 3G / 2G)
LAN ports	...	• 1 x 10/100 Mbps - WAN • 3 x 10/100 Mbps - LAN
Transmitter power	...	≤ 20 dBm @ 2.4 GHz ≤ 23 dBm @ 4G LTE ≤ 24 dBm @ 3G WCDMA ≤ 33 dBm @ 2G GSM
LED indicators	...	Power, WAN, 3 x LAN, LTE, Signal indicator
Network type	...	4G, 3G
LTE	...	✓
QSS	...	—
WDS	...	—
DHCP server	...	✓

Protections	...	<ul style="list-style-type: none"> <li>• WPA-PSK/WPA2-PSK</li> <li>• WPA2-PSK</li> <li>• WPA2-EAP</li> <li>• WPA2-EAP/WPA3-EAP</li> <li>• WPA3-EAP</li> <li>• WPA2-PSK/WPA3-SAE</li> <li>• WPA3-SAE</li> <li>• OWE</li> <li>• AES-CCMP</li> <li>• TKIP</li> <li>• Auto Cipher modes</li> <li>• Client separation</li> <li>• SSID hiding</li> <li>• MAC addresses filtering</li> </ul>
Management interface	...	Web browser, Teltonika RMS application, SMS
Main features	<ul style="list-style-type: none"> <li>• Very easy and quick assembly</li> <li>• Corrosion resistance</li> </ul>	<ul style="list-style-type: none"> <li>• Support for IoT (Internet of Things) systems,</li> <li>• Ability to work as a Hotspot,</li> <li>• Support for VoIP technology,</li> <li>• 2 x SIM socket</li> <li>• DHCP Relay support</li> <li>• DHCP client list</li> <li>• Static / dynamic routing</li> <li>• VPN support</li> <li>• Default address : 192.168.1.1</li> <li>• Configuration using the Teltonika RMS application</li> <li>• WAN Connection Backup - thanks to the fully functional WAN / LAN port, you can use various types of backup connections, including cable, fiber and DSL modems</li> </ul>
Power supply	...	<ul style="list-style-type: none"> <li>• 9 V DC / 1 A (power adapter included)</li> <li>• 9 ... 30 V DC</li> <li>• 9 ... 30 V DC - Passive PoE, Powering from LAN1</li> </ul>
Power consumption	...	≤ 7 W
Operation temp	...	-40 °C ... 75 °C
Permissible relative humidity	...	10 % ... 90 % (non-condensing)
Weight	0.012 kg	0.26 kg
Dimensions	...	110 x 100 x 50 mm
Manufacturer / Brand	...	Teltonika
Guarantee	2 years	2 years