




	SWITCH POE IP-5-11-M2 5-PORT ATTE	SMART LED LIGHTING CONTROLLER WLIGHTBOX-S-PRO/BLEBOX Wi-Fi, 12 ... 24 V DC	SWITCH POE NSW2020-10T-POE-IN 8-PORT UNIVIEW
			
	1274.83 NOK 1274.83 NOK	368.79 NOK 368.79 NOK	1188.94 NOK 1188.94 NOK
Application	...	Works with LED lighting - single-color (MONO) 12-24V LED strips	...
Rated voltage	...	12 ... 24 V DC	...
Maximal total load	...	120 W	...
Total maximal current	...	5 A	...
Number of inputs	...	1	...
LAN ports	<ul style="list-style-type: none"> • 1 x RJ45 10/100 Base-T - Uplink • 5 x RJ45 10/100 Base-T + PoE (802.3af/at) / Passive PoE 	...	<ul style="list-style-type: none"> • 8 x RJ45 10/100 Base-T (8 x PoE (802.3af/at)), • 2 x RJ45 100 Base-T - Uplink
Number of outputs	...	1	...
Connector type	...	screw terminals	...
Management	—	...	—
LED diodes	Power, LAN	...	Link/Act, Power, PoE Max
Wireless	...	Wi-Fi, 2.4 GHz - IEEE 802.11g	...
Mobile phones support	...	<ul style="list-style-type: none"> • The wBox free application on Android • The wBox free application on iOS 	...
Transmission speed	10 / 100 Mbps : 1 Port LAN + 5 LAN & PoE ports	...	<ul style="list-style-type: none"> • 100 Mbps : 2 LAN ports - Uplink, • 10 / 100 Mbps : 8 LAN & PoE ports
MAC addresses table	1k
Maximal output power	<ul style="list-style-type: none"> • 40 W @ Passive PoE - 1 ... 4 ports, • 70 W @ Passive PoE - Port 5, • 30 W @ PoE (802.3af/at) - 1 ... 5 ports 	...	30 W / port PoE 802.3af/at
Maximal total power	96 W	...	88 W
Certificates	CE, FCC
"Index of Protection"	...	IP54	...
Housing	...	<ul style="list-style-type: none"> • Non-halogen plastic, Self-extinguishing • Waterproof, Weatherproof 	Desktop, Metal

Color	...	Black	...
Operation modes	<ul style="list-style-type: none"> • Normal : 100 m @ 10/100 Mb/s - 1 ... 5 ports • Long Range : 280 m @ 10 Mb/s - 1 ... 4 ports ; 100 m @ 10/100 Mb/s - Port 5 • Port LAN 6 - Uplink 	...	<ul style="list-style-type: none"> • Extend : 250 m, 10 Mbps • Default : 100 m, 100 Mbps
Operation temp	...	-20 °C ... 50 °C	0 °C ... 40 °C
Main features	<ul style="list-style-type: none"> • Possible cascading device connection (power transmission between devices using Passive PoE via LAN 5 port) • The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 5 ports • The modular design streamlines service tasks and enables quick and easy system expansion • The raster system of module assembly facilitates the expansion of the device by further modules • The ABOX-M2 mounting enclosure is equipped with 7 cable entries with glands in the 6 x M16 + 1 x M20 arrangement 	<ul style="list-style-type: none"> • Local control by physical button, • schedule, • timer, • remote access, • voice control, • Lighting on/off and brightness control, • Absence mode - enables random turn on and off the lighting simulating the presence of household members, • Omnidirectional antenna Wi-Fi 5 dB, • SMA-RP socket • µWiFi technology support 	<ul style="list-style-type: none"> • EXTEND mode - ports 1, 2, 3, 4, 5, 6, 7, 8 support transmission up to 250 m • High priority ports : 1, 2 • Data Flow Control • Buffer optimization • Metal housing • Possibility to mount to the wall
Power supply	230 V AC - cable terminals	...	52 V DC / 1.8 A (power adapter included)
Weight	0.65 kg	0.094 kg	0.28 kg
Dimensions	226 x 148 x 80 mm	<ul style="list-style-type: none"> • 92 x 52 x 28 mm - without antenna • 230 x 85 x 28 mm - with antenna, vertical • 197 mm - Antenna 	171 x 101 x 26 mm
Manufacturer / Brand	ATTE	BleBox	UNIVIEW
Guarantee	3 years	2 years	2 years