









	RFID PROXIMITY CARD ATLO-104N*P50	SILICONE CAMERA COVER FBS10-B-JMGU	MULTIMEDIA SHELF AX- RTV1	WIRED DOORBELL ATLO- DB-1	POE SWITCH / EXTENDER PFT1300 3-PORT DAHUA	RFID PROXIMITY CARD KT- STD-2 SATEL	EXTENDER HDMI+USB- EX-70-4KV2
							
	16.98 EUR 16.98 EUR	8.40 EUR 8.40 EUR	9.65 EUR 9.65 EUR	4.07 EUR 4.07 EUR	23.53 EUR 23.53 EUR	1.94 EUR 1.94 EUR	178.15 EUR 178.15 EUR
Number of shelves	1
Material	...	Silicon
Listen to the available sounds	
Bearing capacity	10 kg
Signaling mode	Sound signaling
Supported HDMI resolutions	max. 4K UHD @ 60 Hz
Swivel angle adjustment:	---
Number of ring-tones	1
Color	...	Black	Black
In package	50 pcs The price for package
Volume adjustment	---
Distance from mounting surface	3 mm
Standard	Unique EM 125kHz	Unique EM 125kHz	...
"Index of Protection"	IP40
Compatibility	EM4100/4102	EM4100/4102	...
Possibility of programming the serial number (ID)	---	---	...
LAN ports	<ul style="list-style-type: none"> • 1 x RJ45 10/100 Base-T + power input : PoE (802.3af/at), • 2 x RJ45 10/100 Base-T + PoE (802.3af)
Ability to write to internal memory	---	---	...
Serial Number overprint	✓	✓	...
Management	---
LED diodes	LAN, PoE
Transmission speed	10 / 100 Mbps
Maximal transmission range	<ul style="list-style-type: none"> • 60 m - UTP cat. 6, 6A, 7 @ 4K UHD (manufacturer data) • 70 m - UTP cat. 5e @ 1080p (our tests result) • 20 m - UTP cat. 5e @ 4K UHD (our tests result) • 60 m - UTP cat. 6 @ 4K UHD (our tests result)
Maximal output power	<ul style="list-style-type: none"> • 15.4 W @ port PoE - First device • 3 W @ port PoE - Second device in cascade
Power consumption	0.3 W
Main features	<ul style="list-style-type: none"> • Extender also allows to extend an USB 2.0 port, eg. in order to control the recorder using the mouse • Support KVM function, • HDR10 support • Transition of the HDMI signal in the transmitter • EDID support • ESD protection
Range	100 m - Input 100 m - Output
Protections	Overvoltage
Housing	Plastic, DIN, TS-35 rail mounting
Main features	<ul style="list-style-type: none"> • Serial Number Format : 8H10D + WEG24A • Range: ~ 11 cm • The TK-4100 chip 	<ul style="list-style-type: none"> • Possibility to connecting in cascade • The device can function as a LAN network and PoE power extender 	...	<ul style="list-style-type: none"> • Very good image quality with no visible distortions caused by compression, • No delays in video transmission, • No delays in mouse control operations • Designed to continuous operation 24/7
Operation temp. / Relative humidity	-30 ... 65 °C / 10 ... 90 %
Power supply	12 V DC	PoE (802.3af/at)	...	5 V DC / 1 A - 2 pcs (included)
Operation temp	-20 °C ... 60 °C
Manufacturer / Brand	ATLO	DAHUA	...	ATLO	DAHUA	SATEL	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Permissible relative humidity	0 % ... 90 % (non-condensing)
Weight	0.006 kg	0.03 kg	1.33 kg	0.06 kg	0.06 kg	0.009 kg	0.12 kg
Dimensions	86 x 54 x 1 mm	65 x 78 x 76 mm	300 x 250 x 38 mm	62 x 88 x 24 mm	80 x 51 x 23 mm	86 x 54 x 2 mm	85 x 75 x 20 mm - Transmitter or receiver dimensions
Guarantee	2 years	2 years	2 years	3 years	3 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00