




	COVER PLATE A19-MASK	AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE76H0T-ITPFS(2.8mm) - 5 Mpx Hikvision	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1500T-A-0280B-S2 - 4.7 Mpx 2.8 mm DAHUA
			
	2.24 EUR 2.24 EUR	51.61 EUR 51.61 EUR	81.90 EUR 81.90 EUR
Standard	...	AHD / HD-CVI / HD-TVI / CVBS	AHD, HD-CVI, HD-TVI, CVBS
Sensor	...	Progressive Scan CMOS	1/2.7 " CMOS
Matrix size	...	5 Mpx	5 Mpx
Resolution	...	<ul style="list-style-type: none"> • 2560 x 1944 - 5 Mpx @ AHD / HD-TVI - 20 fps • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI - 25 fps • 1920 x 1080 - 1080p @ HD-TVI - 25 fps • 960 x 576 - 960H @ PAL 	2880 x 1620 - 4.7 Mpx - HD-CVI only : Aspect Ratio 16 : 9 , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p 960 x 576 - 960H
Lens	...	2.8 mm	2.8 mm
View angle	...	86 °	<ul style="list-style-type: none"> • 111 ° (manufacturer data) • 104 ° - HD-CVI, 91 ° - HD-TVI, 90 ° - AHD (our tests result)
Range of IR illumination	...	20 m	30 m
IR illuminator power adjustment	...	Automatic	Automatic
IR illuminator support	...	ICR - Movable InfraRed filter	...
Video output	...	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
S/N ratio	> 65 dB
Audio	...	<ul style="list-style-type: none"> • Microphone built-in • Audio support via coaxial cable 	Microphone built-in, HD-CVI only

Main features	...	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • AGC - Automatic Gain Control • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • Auto White Balance • Mirror - Mirror image • Sharpness - sharper image outlines 	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Sharpness - sharper image outlines • AGC - Automatic Gain Control • Privacy zones • Mirror - Mirror image • Auto White Balance
OSD menu	...	OSD menu available via recorder	✓
Power supply	...	12 V DC / 310 mA	12 V DC / 270 mA
Power consumption	...	≤ 3.7 W	≤ 3.2 W
Housing	...	Dome, Plastic	Compact, Metal
Color	Black	White	White
"Index of Protection"	...	—	IP67
Vandal-proof	...	—	...
Operation temp	...	-40 °C ... 60 °C	-40 °C ... 60 °C
Weight	0.19 kg	0.15 kg	0.37 kg
Dimensions	218 x 39 x 2 mm	Ø 85 x 79 mm	Ø 73 x 176 mm
Manufacturer / Brand	DELTA	Hikvision	DAHUA
SAP Code	...	300613327	...
Guarantee	3 years	3 years	3 years