

	50 dB (AGC off)	
Range of IR illumination	...	30 m
Image compression method	...	H.264 / MJPEG
Bitrate	...	5 ... 10240 kbps - H.264 32 ... 12288 kbps - MJPEG
Main stream frame rate	...	<ul style="list-style-type: none"> • 20 fps @ 4.0 Mpx • 25 fps @ 3.0 Mpx
Network interface	...	10/100 Base-T (RJ-45)
Network protocols	...	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS, Bonjour, IEEE 802.1x
WEB Server	...	Built-in, NVR compliance
Max. number of on-line users	...	10
ONVIF	...	2.42
Audio	...	—
Mobile phones support	...	Port 37777 <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Default IP address	...	192.168.1.108
Default admin user / password	...	admin / admin
Web browser access ports	...	80, 37777
PC client access ports	...	37777
Mobile client access ports	...	37777
Port ONVIF	...	80
RTSP URL	...	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
RS-485 interface	...	—
Alarm inputs / outputs	...	—
Main features	...	<ul style="list-style-type: none"> • ICR - Movable InfraRed filter • 3D-DNR - Digital Noise Reduction • D-WDR - Wide Dynamic Range • BLC - configurable Back Light Compensation • WB - White Balance (ATW/AWB/manual/indoor/outdoor) • Day/Night mode (color/b&w/auto) • Motion Detection • Configurable Privacy Zones - Mirror - Mirror image
Power supply	12 V DC / 2.5 A (power adapter included)	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 620 mA
Power consumption	<ul style="list-style-type: none"> • ≤ 32 W (typical) • ≤ 0.3 W (in standby mode) 	≤ 7.5 W



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Housing	...	Metal
Color	...	White
"Index of Protection"	...	IP66
Operation temp	...	-30 °C ... 60 °C
Weight	2.97 kg (with stand)	0.382 kg
Dimensions	<ul style="list-style-type: none"> • 543 x 415 x 160 mm (with stand) • 543 x 335 x 40 mm (without stand) 	165 x 73 x 67 mm
Manufacturer / Brand	DAHUA	BCS
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00