






	MULTIMEDIA SHELF AX-RTV1	ALARM CONTROL PANEL ENCLOSURE OPU-4-P SATEL	HUB USB 3.0 CT2U3-13AB-EU-WH-BP 1 m	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HDW1500TRO-0280B-S2 - 5 Mpx 2.8 mm DAHUA	WIRELESS PIR DETECTOR MPD-300 SATEL
					
	3788.57 HUF 3788.57 HUF	9142.86 HUF 9142.86 HUF	14485.71 HUF 14485.71 HUF	22285.71 HUF 22285.71 HUF	11333.33 HUF 11333.33 HUF
Number of shelves	1
Support	Satel MICRA
Bearing capacity	10 kg
Transformer	...	40 or 60 VA (not included)
Swivel angle adjustment:	—
Frequency range	433.05 ... 434.79 MHz
Standard	HD-CVI, HD-TVI, AHD, CVBS	...
Radio communication range (at open area)	max. 200 m
Distance from mounting surface	3 mm
Sensor	1/2.7 " Progressive Scan CMOS	...
Connectors	<ul style="list-style-type: none"> • 1 x Socket - USB-B 3.0 • 13 x socket - USB-A • 1 x Power socket - 5.5/2.1 socket
Place for battery	...	7 Ah / 12 V
Matrix size	5 Mpx	...
Detection angle / Detection range	90 ° / 16 m
Length of the cable	1 m
Tamper protection	...	Tamper detection - opening the enclosure, removing from mounting surface
Pet immunity	≤ 15 kg
USB standard	3.0
Current-carrying capacity of TAMPER output	...	—
Battery lifetime	~ 3 years
Operation temp	...	-10 °C ... 40 °C	-10 °C ... 55 °C
Recommended installation height	2.4 m
Application	...	INTEGRA, VERSA, CA-6-P, CA-10-P, GSM Module
Power adapter included	...	—

Main features	<ul style="list-style-type: none"> • Solid workmanship • LED indication • Each socket has a separate switch 	...	<ul style="list-style-type: none"> • digital detection algorithm with temperature compensation for high immunity to false alarms and repeatability of parameters • ability to change sensitivity to match optimum detector parameters to the protected space • Interchangeable Fresnel lenses • The LED to indicate violations in test mode, easy start-up and later maintenance of the system • Tamper detection - opening the enclosure, removing from mounting surface • energy management system to enable many years of operation without having to replace the CR123A Lithium battery
Resolution	2880 x 1620 - 5 Mpx, HD-CVI only : Aspect Ratio 16 : 9 , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p, HD-CVI only 960 x 576 - 960H, PAL	...
Range of IR illumination	25 m	...
IR illuminator power adjustment	Automatic	...
Lens	2.8 mm	...
View angle	<ul style="list-style-type: none"> • 111 ° (manufacturer data) • 105 ° (our tests result) 	...
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	...
Audio	—	...
Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • Day/night mode • AGC - Automatic Gain Control • ICR - Movable InfraRed filter • Auto White Balance • Privacy zones • Mirror - Mirror image • Sharpness - sharper image outlines 	...
OSD menu	OSD menu available via DAHUA recorder	...
Power supply	...	—	12 V DC / 5 A (included)	12 V DC / 250 mA	CR123A 3 V
Power consumption	≤ 3 W	...
Housing	Plastic	Dome, Plastic	...
"Index of Protection"	...	IP20	...	IP50	...
Color	Black	White	...
Vandal-proof	—	...
Operation temp	-40 °C ... 50 °C	...
Weight	1.33 kg	0.9 kg	0.191 kg	0.16 kg	0.090 kg
Dimensions	300 x 250 x 38 mm	266 x 286 x 100 mm	235 x 62 x 28 mm	Ø 97 x 93 mm	63 x 96 x 49 mm
Manufacturer / Brand	...	SATEL	ORICO	DAHUA	SATEL

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Guarantee	2 years	2 years	2 years	3 years	2 years
-----------	---------	---------	---------	---------	---------



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00