





	INSULATION STRIPPER HT-766	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR IDS-7204HUHI-M1/S(C) 4 CHANNELS ACUSENSE Hikvision	WORK GLOVES WG-422/L Bee-Smart WONDER GRIP	CABLE GLAND ML-147 IP68 M16 x 1.5
				
	6.29 EUR 6.29 EUR	224.87 EUR 224.87 EUR	5.49 EUR 5.49 EUR	0.55 EUR 0.55 EUR
"Index of Protection"	IP68
Type (size)	M16 x 1.5
Cable diameter	Ø 4 ... 8 mm
Standard	...	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP
Material	Plastic (ABS)
Application	Wire - 0.2 ... 6 mm ² (24 AWG ... 10 AWG)	...	<ul style="list-style-type: none"> • Construction and public works, • Warehousing - packing and logistics, • DIY, • Assembly 	...
Video inputs	...	4 pcs BNC - AHD / HD-CVI / HD-TVI / CVBS
Material	Metal / PET	...	Polyester + latex coating (palm coated)	...
Video outputs	...	1 pcs HDMI 1 pcs VGA 1 pcs CVBS - BNC socket
Audio inputs	...	1 pcs CINCH, Coaxial audio - Audio from cameras
Audio outputs	...	1 pcs CINCH
Main features	<ul style="list-style-type: none"> • Breaking force adjustment knob, • Self-adjusting mechanism according to wire size provides excellent wire stripping without damaging the conductor, • Adjustable stop with lengths scale, • Cutter, • High durability tool, made from high quality materials 	...	<ul style="list-style-type: none"> • Thermal protection : 100 °C (X1XXXX), • Ergonomics and comfort • High grip • Soft coating 	...
Image compression method	...	H.265+ / H.265 / H.264 / H.264+
Supported norms	<ul style="list-style-type: none"> • EN 388:2016 - Mechanical protection 3131X • EN 407:2004 - Thermal protection X1XXXX 	...
Size	9 / L	...
Image records resolutions	...	<ul style="list-style-type: none"> • HD-TVI : 8.3 Mpx 4K UHD - 3840 x 2160 1 CH only , 8M-N - 1920 x 2160 2,3,4 CH only , 5 Mpx - 2560 x 1944 , 3.7 Mpx - 2560 x 1440 , 3 Mpx - 1920 x 1536 , 1080p - 1920 x 1080 , 720p - 1280 x 720 , • AHD : 5 Mpx - 2560 x 1944 , 3.7 Mpx - 2560 x 1440 , 1080p - 1920 x 1080 , 720p - 1280 x 720 , • HD-CVI : 3.7 Mpx - 2560 x 1440 , 1080p - 1920 x 1080 , 720p - 1280 x 720 , • PAL : 960H - 960 x 576 , • IP : max. 8 Mpx - 3840 x 2160

Recording speed adjustment	...	8 Mpx IP @ 1 ... 25 fps 8 Mpx @ 1 ... 8 fps 8M-N @ 1 ... 15 fps 5 Mpx @ 1 ... 12 fps 4 Mpx @ 1 ... 15 fps 3 Mpx @ 1 ... 18 fps 1080p @ 1 ... 25 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps for each channel
Operation modes	...	4 x HD-TVI / AHD / HD-CVI / CVBS / IP + 4 x IP
Recording modes	...	Manual, Sensor, Motion detection, Schedule
Supported hard drives	...	1 x 10 TB SATA
External storage devices backup	...	Backup to USB drive (pendrive, external drive)
Searching and playback the records	...	Records searching: timeline or file list. Playback: forward, fast, slow. Playback max. 4 cameras in the same time
Network interface	...	1 x RJ-45 - 10/100 Base-TX
Bitrate	...	32 ... 10240 kbps
Network functions	...	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters
Network protocols	...	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP, HTTPS, ONVIF
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • iOS: Free application Hik-Connect
Default IP address	...	DHCP or 192.168.1.64
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80
PC client access ports	...	554 RTSP, 8000
Mobile client access ports	...	8000
Port ONVIF	...	80
RTSP URL	...	• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream
Alarm inputs / outputs	...	—
PTZ control	...	• Control compatible with coax HD-TVI Hikvision • RS-485 - PELCO-D/P
Motion Detection	...	2.0
USB	...	2 x USB 2.0
Mouse support	...	✓
IR remote controller in the set	...	—
Main features	...	• DVR from the AcuSense series • Intelligent image analysis : crossing the line (tripwire), intrusion, Deep Learning technology • Smart motion detection (with recognizing people and vehicles) • Filtering of false alarms based on the recognition of persons and vehicles
Power supply	...	12 V DC / 1.5 A (power adapter included)
Color	...	Black	Black + Blue	...
Weight	0.35 kg	1.1 kg	...	0.007 kg
Dimensions	205 x 93 x 33 mm	315 x 250 x 45 mm	...	33 x 24 x 24 mm
Supported languages	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Greek, Spanish, Dutch, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
Manufacturer / Brand	...	Hikvision	WONDER GRIP	...
SAP Code	...	300226972
Guarantee	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00