

	ACCESS POINT 4G LTE +ROUTER TL-MR6400 300Mb/s TP-LINK	SWITCHING ADAPTER 24V/3A/GPV	WIRELESS REMOTE CONTROL WITH KEYBOARD KS-3 Air Mouse 2.4 GHz Blow	STYROFOAM PLUG SM-50/EPN*P4 Elektro-Plast	EXPANSION PLUG KS-10/6X100 KLIMAS	AC POWER SUPPLY ADAPTER TR-60VA/NORATEL SATEL
						
	899.46 NOK 899.46 NOK	197.83 NOK 197.83 NOK	128.55 NOK 128.55 NOK	10.97 NOK 10.97 NOK	2.99 NOK 2.99 NOK	399.46 NOK 399.46 NOK
Operating frequency	2.4 GHz
Adapter type	...	Switching	Transforming
Operation range	~ 10 m
Power voltage	...	90 ... 264 V AC	230 V AC
In package	4 pcs The price for package
Material	• Expansion plug, Polypropylene • Screw, Steel galvanized	...
Length	49 mm
Drilling diameter	10 mm	...
Frequency range	2.4 GHz	47 ... 63 Hz	47 ... 63 Hz
Expansion plug length	60 mm	...
Output voltage	...	24 V DC	18 V, 20 V AC
Output voltage tolerance	...	± 5 %
EN norm	EN61558-2-6
Diameter	Ø 20 mm / Ø 24 mm
Maximal load	...	3 A	3 A
Test voltage between PRI/SEC	AC 4kV RMS
Thickness of the Styrofoam	≥ 50 mm
Antenna type	2 x WiFi built-in , 2 x 4G LTE - 2 x SMA socket - Possibility to connect the wire antenna
Screw dimensions	Ø 6 x 100 mm, SW-10	...
Safety class	II
Efficiency	...	86 %
Number of outputs	...	1 pcs
Isolation class	B (130°C)
Standards	802.11n/g/b IEEE 802.3/3u
Diameter of the screw	Ø 4 mm ... Ø 5 mm
Application	• Concrete • Solid clay brick • Solid sand-lime brick	...
Output power	...	72 W	60 VA
Protections	...	• Overload • Short-circuit • Overvoltage
Housing	Plastic
Color	Black
Application	• to alarm systems powering • to automatic systems • to low-voltage light installation powering
Output	2 pcs
Housing type	...	Plastic, Waterproof
Baud rates	11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps LTE : 150 Mbps
"Index of Protection"	...	IP67	IP43
Current consumption	• 8 ... 16 mA (operation) • 6 mA (Standby mode)
Modulation type	DBPSK, DQPSK, CCK OFDM, 16-QAM, 64-QAM
LAN ports	• 1 x 10/100 Mbps - LAN/WAN • 3 x 10/100 Mbps - LAN
Receiver sensitivity	• 11g 54M: -74dBm • 11n HT20: -71dBm • 11n HT40: -67dBm
LTE	✓
QSS	✓

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

WDS	✓
Power supply	9 V DC / 1 A (power adapter included)	...	• built-in battery • Charging via micro USB port
Operation temp	0 °C ... 40 °C	-30 °C ... 70 °C
Permissible relative humidity	max. 95 % (non-condensing)
Main features	<ul style="list-style-type: none"> • SIM socket • WPS/RESET button 	<ul style="list-style-type: none"> • Protection class : II • Box casing designed to wall mounting 	<ul style="list-style-type: none"> • Air Mouse function - The built-in gravity sensor allows you to control the mouse cursor on the device screen by holding the remote control and making movements in the air - this solution does not require any flat surface • Backlit full keyboard in QWERTY standard • Remote control - Basic operation of functions such as: volume control, menu operation, channel selection, turning on and off the connected device • The ergonomic shape • Illuminated buttons • Plug & Play • Compatible with Windows, Mac OS, Linux, Android systems • Cooperation with DAHUA, HIKVISION recorders • USB cable included
Weight	0.354 kg	0.36 kg	0.053 kg	0.004 kg / 1 pcs	...	1.23 kg
Dimensions	202 x 141 x 34 mm	162 x 42 x 33 mm	<ul style="list-style-type: none"> • 151 x 45 x 14 mm • 0.5 m (cable length) 	124 x 72 x 67 mm
Manufacturer / Brand	TP-LINK	...	Blow	Elektro-Plast Nasielsk	KLIMAS	SATEL
Guarantee	3 years	3 years	2 years	2 years	2 years	2 years