



	ROUTER ARCHER-C6U 2.4 GHz, 5 GHz 300 Mbps + 867 Mbps TP-LINK	HANGING RACK CABINET EPRADO-R19-15U/600-BLUE	SWITCH POE PFS3006-4ET-36 4-PORT DAHUA
			
	550.04 NOK 550.04 NOK	1475.12 NOK 1475.12 NOK	494.97 NOK 494.97 NOK
Internal width	...	19 "	...
Internal height	...	15 U	...
Frequency range	2.4 GHz, 5 GHz
Internal depth	...	545 mm	...
External width	...	600 mm	...
External height	...	770 mm	...
Antenna type	<ul style="list-style-type: none"> • 4 x Omnidirectional antenna - Integrated, • 1 x Internal antenna
External depth	...	600 mm	...
Holes for fan coolers	...	105 x 105 mm (2 places)	...
Bearing capacity	...	60 kg	...
Color	...	Black RAL9004	...
Baud rates	300 Mbps + 867 Mbps
Standards	IEEE 802.11 b/g/n @ 2.4 GHz IEEE 802.11 a/n/ac @ 5 GHz	...	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3af, IEEE 802.3at
Door	...	<ul style="list-style-type: none"> • Front: glass • Side: metal, snap-in 	...
Management	—
LAN ports	4 x 10/100/1000 Mbps LAN 1 x 10/100/1000 Mbps Uplink	...	<ul style="list-style-type: none"> • 2 x RJ45 10/100 Base-TX - Uplink, • 4 x RJ45 10/100 Base-TX (4 x PoE (802.3af/at))
LED diodes	Power, Link/Act, PoE
Transmission speed	10 / 100 Mbps : 2 LAN ports + 4 LAN & PoE ports
LED indicators	Power, 2.4 GHz WLAN, 5 GHz WLAN, Ethernet, WAN, USB
Maximal output power	30 W / port PoE
Maximal total power	36 W
MAC addresses table	2k
Operation modes	<ul style="list-style-type: none"> • Extend On : 250 m, 10 Mbps • Extend Off : 100 m, 100 Mbps
Certificates	CE, FCC

Receiver sensitivity	2.4 GHz : <ul style="list-style-type: none"> • 11g 6M : -94 dBm • 11g 54M : -77 dBm • 11n HT20 MCS7 : -75 dBm • 11n HT40 MCS7 : -72 dBm 5 GHz : <ul style="list-style-type: none"> • 11a 6M : -94 dBm • 11a 54M : -77 dBm • 11ac VHT20 MCS0 : -98 dBm • 11ac VHT20 MCS8 : -72 dBm • 11ac VHT40 MCS0 : -92 dBm • 11ac VHT40 MCS9 : -66 dBm • 11ac VHT80 MCS0 : -89 dBm • 11ac VHT80 MCS9 : -63 dBm
DDNS	✓
DHCP server	✓
Firmware update	✓
Protections	WEP 64/128-bit, WPA/WPA2, WPA-PSK/WPA2-PSK DoS attacks protection, SPI network firewall, domain filtering, IP and MAC filtering, IP and MAC binding
Management interface	Web browser, TP-LINK Tether
Transmitter power	max. 20 dBm @ 2.4 GHz max. 23 dBm @ 5 GHz
Power supply	12 V DC / 1.5 A (power adapter included)	...	100 V ... 240 V AC

Main features	<ul style="list-style-type: none"> • MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network • Beamforming (TxBF) - technology that allows to create a beam of radio waves in order to improve the quality of connection with client devices located further away from the signal source • Airtime Fairness - technology that improves network performance when multiple clients with different data rates appear in it • Firewall • Internet access filtering • Static / dynamic routing • Built-in 4-port switch • Access Point • The WPS function allows to easy establish an encrypted connection • QoS • Access control • Remote management • DMZ • UPnP • Port forwarding • parental control • Guest Network - a separate and secure network for guests • DHCP client list • VPN networks: Open VPN, PPTP VPN • SSID hiding • IPv6 compliance • Smooth transmission in HD quality - IGMP Proxy/Snooping, Bridge VLAN, Tag VLAN functions contribute to optimal IPTV transmission • The USB 2.0 built-in storage port supports drive, media server, FTP server and print server sharing functions 	<ul style="list-style-type: none"> • Cable entries are placed from the top and bottom • Removable side panels • Possibility to unscrew the rear panel • Possibility to mount the door as left or right • Mounting rail spacing : 490 mm • 2 keys included • Rack rails to mounting the devices - 4 pcs 	<ul style="list-style-type: none"> • PoE power mode : The device supports 8-pin power supply • EXTEND mode - ports PoE1, PoE2, PoE3, PoE4 support transmission up to 250 m • Watchdog PoE / PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected • protection against lightning discharges and voltage differences and strokes between devices • Kensington Lock
---------------	--	---	---



Operation temp	0 °C ... 40 °C	...	-10 °C ... 55 °C
Permissible relative humidity	10 % ... 90 % (non-condensing)
Weight	0.33 kg	29.5 kg	0.56 kg
Dimensions	215 x 125 x 30 mm	...	194 x 108 x 35 mm
Manufacturer / Brand	TP-LINK	EPRADO	DAHUA
Guarantee	3 years	3 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00