



	IEC PLUG WPW-307	ANTENNA AMPLIFIER AWS-141M AMS	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR BCS-V-XVR0801-A1 8 CHANNELS BCS View	STYROFOAM PLUG SM-140/EPN*P4 Elektro-Plast
				
	0.95 GBP 0.95 GBP	18.16 GBP 18.16 GBP	202.47 GBP 202.47 GBP	2.60 GBP 2.60 GBP
Connector type	IEC Straight plug
Frequency range	...	87 MHz ... 694 MHz
Attachment of connector elements	—
In package	4 pcs The price for package
Shield fastening	Twisting-on
Number of inputs/outputs	...	1 / 1
Length	140 mm
Wire mounting	Pressing
Standard	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP	...
Input/output impedance	...	75 Ω
Application	Coaxial cable
Connectors type	...	"F"
Diameter	Ø 20 mm / Ø 24 mm
Cable diameter	min. 6.6 mm max. 6.9 mm
Thickness of the Styrofoam	≥ 140 mm
Impedance	75 Ω
Gain	...	20 / 24 dB ± 2 dB
Material	Metal
Video inputs	8 pcs BNC - AHD / HD-CVI / HD-TVI / CVBS	...
Watertightness	✓
Diameter of the screw	Ø 4 mm ... Ø 5 mm
Gain adjustment	...	0 ... 10 dB ± 2 dB
S/N ratio	...	≤ 4 dB
Example of application	• RG6 • HF EK • Triset113
Video outputs	1 pcs HDMI 1 pcs VGA 1 pcs CVBS - BNC socket	...
Maximum output level	...	105 dB μ V (2kTV)
IMA3 60dB	...	99 dB μ V
IMA2 60dB	...	86 dB μ V
Return loss	...	≥ 10 dB
Audio inputs	1 pcs CINCH, Coaxial audio - Audio from cameras	...
Pre-amplifiers powering	...	✓
Audio outputs	1 pcs CINCH	...
Main features	• Very easy and quick assembly • Corrosion resistance • The die-cast metal body provides effective shielding and high mechanical resistance	• Built-in pass-through filter 87 ... 694 MHz • Built-in LTE filter
Image compression method	H.265+ / H.265 / H.264 / H.264+	...
Operation temp	...	-25 °C ... 55 °C

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Image records resolutions	<ul style="list-style-type: none"> • HD-TVI : 4M-N - 1280 x 1440 , 3 Mpx - 1920 x 1536 1,2 CH only , 1080p - 1920 x 1080 , 960 x 1080 - 1080N , 720p - 1280 x 720 , • AHD / HD-CVI : 4M-N - 1280 x 1440 , 1080p - 1920 x 1080 , 960 x 1080 - 1080N , 720p - 1280 x 720 , • PAL : 960H - 960 x 576 , • IP : max. 6 Mpx - 3072 x 2048 	...
Recording speed adjustment	6 Mpx IP @ 1 ... 25 fps 4M-N @ 1 ... 15 fps 3 Mpx @ 1 ... 15 fps 1080p @ 1 ... 15 fps 1080N @ 1 ... 25 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps for each channel	...
Operation modes	8 x HD-TVI / AHD / HD-CVI / CVBS / IP + 4 x IP	...
Recording modes	Manual, Sensor, Motion detection, Schedule	...
Supported hard drives	1 x 10 TB SATA	...
External storage devices backup	Backup to USB drive (pendrive, external drive)	...
Searching and playback the records	Records searching: timeline or file list. Playback: forward, fast, slow. Playback max. 4 cameras in the same time	...
Network interface	1 x RJ-45 - 10/100 Base-TX	...
Bitrate	32 ... 6144 kbps	...
Network functions	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters	...
Network protocols	TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP, HTTPS, ONVIF	...
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) • Android: Free application BCS View • iOS (iPhone): Free application BCS View	...
Default IP address	DHCP or 192.168.1.64	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80	...
PC client access ports	554 RTSP, 8000	...
Mobile client access ports	8000	...
Port ONVIF	80	...
RTSP URL	<ul style="list-style-type: none"> • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream 	...
Alarm inputs / outputs	—	...
PTZ control	<ul style="list-style-type: none"> • Control compatible with coax HD-TVI • RS-485 - PELCO-D/P 	...
Motion Detection	Split the screen into zones : 22 x 18 motion zones	...
USB	2 x USB 2.0	...
Mouse support	✓	...
IR remote controller in the set	—	...
Power supply	...	12 V DC / 150 mA (power adapter included)	12 V DC / 1.5 A (power adapter included)	...
Color	Black	...
Weight	0.012 kg	0.08 kg	1.2 kg	0.015 kg / 1 pcs
Dimensions	Ø 10 x 40 mm	111 x 64 x 28 mm	315 x 250 x 45 mm	...


 DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Supported languages	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Greek, Spanish, Dutch, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian	...
Manufacturer / Brand	TELMOR	AMS	BCS View	Elektro-Plast Nasielsk
Guarantee	2 years	3 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00