



	PLUG BNC-W/55-HAND*P10	NVR TC-R3110 SPEC:I/B/P8/K/V3.1 10 CHANNELS, 8 PoE TIANDY
		
	45.11 NOK 45.11 NOK	5740.84 NOK 5740.84 NOK
Standard	...	IP
Supported resolutions	...	max. 8 Mpx
In package	10 pcs The price for package	...
Video outputs	...	1 pcs HDMI 4K 1 pcs VGA
Audio support	...	4 Channels - Audio from cameras
Connector type	BNC Straight plug	...
Audio inputs	...	1 pcs
Attachment of connector elements	—	...
Audio outputs	...	1 pcs
Shield fastening	Twisting-on	...
Wire mounting	Pressing	...
Application	Coaxial cable	...
Cable diameter	max. 5.5 mm	...
Image compression method	...	S+265 / H.265 / S+264 / H.264
Impedance	75 Ω	...
Material	Metal	...
Supported hard drives	...	1 x 10 TB SATA
Recording modes	...	Manual, Motion Detection, Schedule
External storage devices backup	...	Backup to USB drive (pendrive, external drive)
Example of application	<ul style="list-style-type: none"> • YAP • K-60 • RG59 • YWDX 	...
Searching and playback the records	...	<ul style="list-style-type: none"> • Records searching: by time and events type. Records playback: forward, backward, fast, slow • Advanced searching (to the one second accuracy) • max. 16 channel synchronous playback
Main features	<ul style="list-style-type: none"> • Wide frequency range • Corrosion resistance • Very easy and quick installation without any tools 	...
Network interface	...	1 x RJ-45 - 10 / 100 Mbps

Network functions	...	Full support via network, Remote records copying, Web-Server built-in
ONVIF	...	✓
Bitrate	...	max. 80 Mbps
Default admin user / password	...	admin / - The administrator password should be set at the first start
Default IP address	...	192.168.1.3
RTSP URL	...	rtsp://user:password@192.168.1.3:554/1/1 - Main stream rtsp://user:password@192.168.1.3:554/1/2 - Sub stream
Web browser access ports	...	80, 443, 3000, 3001, 3002, 23002
PC client access ports	...	3000, 3001
Mobile client access ports	...	3000, 3001
Mobile phones support	...	Port no.: 3000 or access by a cloud (P2P) • Android: Free application EasyLive Plus • iOS (iPhone): Free application EasyLive Plus
Access from PC	...	Port no.: 3000 or access by a cloud (P2P) - PC: Free application Easy7 Smart Client Express
Alarm inputs / outputs	...	4 / 1
Motion Detection	...	✓
Intelligent image analysis	...	—
USB	...	2 x USB 2.0
Mouse support	...	✓
IR remote controller in the set	...	—
Main features	...	Support for Intelligent Image Analysis function, available in TIANDY cameras : • crossing the line (tripwire) • double crossing the line • abandoned/missing object • detection of loitering in a given area • running • parking detection • heat map • detection of people gathering • protective helmet detection • detection of persons on duty • signal loss indication • detection of persons on duty • people counting • face detection
Switch PoE	...	8-port PoE Switch built-in, 30 W / Channel - PoE
Maximum total switch load	...	70 W

Power supply	...	48 V DC / 1.875 A (power adapter included)
Weight	0.011 kg	0.93 kg
Dimensions	Ø 14 mm x 36 mm	255 x 239 x 45 mm
Supported languages	...	Polish, English, Albanian, Arabic, Spanish, Korean, Russian, French, Hebrew, German, Dutch, Portuguese, Thai, Ukrainian, Vietnamese, Italian
Manufacturer / Brand	...	TIANDY
Guarantee	2 years	3 years