



| | | |
|----------------------------|---|---|
| | HUB USB 3.0 HUB-USB3.0-1/4 55 cm | WHOLE HOME WI-FI SYSTEM CUDY-M1200/2 2.4 GHz, 5 GHz, 300 Mbps + 867 Mbps CUDY |
| |  |  |
| | 6.19 EUR 6.19 EUR | 53.62 EUR 53.62 EUR |
| Number of devices included | ... | 2 pcs |
| Frequency range | ... | 2.4 GHz, 5 GHz , |
| Antenna type | ... | 2 x Omnidirectional antenna - embedded |
| Connectors | <ul style="list-style-type: none"> • 1 x socket - USB 3.0 Micro B • 4 x socket - USB 3.0 A • 1 x Power socket - 1.35 / 3.50 mm | ... |
| Length of the cable | 55 cm | ... |
| USB standard | 3.0 | ... |
| Standards | ... | IEEE 802.11 b/g/n @ 2.4 GHz , IEEE 802.11 a/n/ac @ 5 GHz |
| Baud rates | ... | 300 Mbps + 867 Mbps |
| LAN ports | ... | 1 x 10/100 Mbps - WAN 1 x 10/100 Mbps - LAN |
| LED indicators | ... | Power / System, Link/Act |
| DDNS | ... | ✓ |
| DHCP server | ... | ✓ |
| Firmware update | ... | ✓ |
| Protections | ... | WEP, WPA/WPA2, WPA-PSK/WPA2-PSK |
| Management interface | ... | Web browser |
| Operation modes | ... | <ul style="list-style-type: none"> • Router, • AP, • Wi-Fi Extender, • WISP |
| Transmitter power | ... | < 20 dBm @ 2.4 GHz < 23 dBm @ 5 GHz |
| Power supply | ... | 12 V DC / 1 A (power adapter included) |

| | | |
|-------------------------------|---|--|
| Main features | <ul style="list-style-type: none"> • Solid workmanship • It can be used as a charger for multiple devices when connected to an external power source via the 3.50 / 1.35 mm socket • LED indication • The cable included in the kit: USB 3.0 A plug / USB 3.0 Micro B plug • Each socket has a separate switch | <ul style="list-style-type: none"> • Support for CUDY Whole Home Mesh technology • Pairing button • RESET button • WMM (Wi-Fi Multimedia) • WAN : Fixed, or dynamic IP address, PPPoE • DHCP : DHCP server, DHCP client list, address reservation • Guest Network - a separate and secure network for guests • NAT : Port forwarding, Port Triggering, UPnP, DMZ • VPN networks: PPTP, L2TP, OpenVPN, WireGuard, IPSec, Zerotier • Access control • Remote management • IPv6 compliance • Supports max. 100 devices • Indoor coverage area : 280 m² |
| Operation temp | ... | 0 °C ... 40 °C |
| Permissible relative humidity | ... | max. 85 % (non-condensing) |
| Weight | 0.044 kg | 0.28 kg |
| Dimensions | 105 x 36 x 25 mm | Ø 110 x 155 mm |
| Manufacturer / Brand | ... | CUDY |
| Guarantee | 2 years | 2 years |