

	VIDEO DOORPHONE MODULE DS-KD8003- IME1(B)/EU Hikvision	AHD, HD-CVI, HD-TVI, PAL CAMERA APTI-H14C9-2812 - 720p 2.8 ... 12 mm
	187.15 EUR 187.15 EUR	33.95 EUR 33.95 EUR
Compatibility	Hikvision - DS-KD-xx	...
Doorbell button	1 pcs	...
Standard	...	AHD, HD-CVI, HD-TVI, PAL
Sensor	2.1 Mpx CMOS	1/3 " Sony CMOS IMX225
Digital Image Processor	...	HTC960E
Camera resolution	1920 x 1080 - 1080p	...
Matrix size	...	1.3 Mpx
Camera view angle	146 °	...
Image compression method	H.264	...
IR illuminator	✓	...
Ethernet	10/100 Mb/s	...
Network protocols	TCP/IP, RTSP	...
Alarm inputs	4 pcs	...
Relay outputs	2 x NO/NC	...
Resolution	...	1280 x 720 - 720p, AHD-M, HD-CVI, HD-TVI , 960 x 576 - 960H, PAL
Range of IR illumination	...	• 90 m (manufacturer data) • 60 m (our tests result)
IR illuminator power adjustment	...	Automatic
Lens	...	2.8 ... 12 mm, 2 Mpx
Main features	<ul style="list-style-type: none"> • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Noise suppression and echo cancellation, • Tamper detection - removing from mounting surface, • Installation of DS-KD-xx series modules takes place in dedicated DS-KD-ACF series housings (flush-mounted housings) and DS-KD-ACW series housings (surface-mounted housings) 	...

View angle	...	<ul style="list-style-type: none"> • 81 ° ... 23 ° (manufacturer data) • 78 ° ... 33 ° (our tests result)
S/N ratio	...	> 50 dB
Operation temp	-40 °C ... 60 °C	...
Video output	...	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI / PAL - selectable by switch
Main features	...	<ul style="list-style-type: none"> • ICR - Movable InfraRed filter • DNR - Digital Noise Reduction • WDR - Wide Dynamic Range • AGC - Automatic Gain Control • Auto White Balance • Sharpness - sharper image outlines
OSD menu	...	✓
"Index of Protection"	IP65	IP66
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC 	12 V DC / 570 mA
Power consumption	≤ 5 W	≤ 6.8 W
Housing	Metal	Compact - Metal
Color	Black	Graphite
Operation temp	...	-20 °C ... 50 °C
Weight	0.38 kg	0.65 kg
Dimensions	100 x 98 x 44 mm	305 x 115 x 97 mm
SAP Code	305303873	...
Supported languages	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Romanian, Serbian, Slovak, Turkish, Ukrainian, Hungarian, Vietnamese, Italian	English, Chinese Traditional, Chinese Simplified, French, Greek, Spanish, Korean, Portuguese, Russian, Italian
Manufacturer / Brand	Hikvision	APTI
Guarantee	3 years	2 years