



	POWER DISTRIBUTION UNIT ACAR-F5/FA/RACK	BOX FOR FLUSH-MOUNTED CONNECTIONS FOR HOUSEHOLD APPLIANCES PK-AGD/2/EPN Elektro-Plast
		
	27.14 EUR 27.14 EUR	15.36 EUR 15.36 EUR
Rated voltage	230 V AC / 50 Hz	...
Nominal load current	max. 10 A (total)	...
Maximal total load	2300 W	...
Number of terminals	...	5 pcs : 3 x 6 mm ² - Quick-connector
"Index of Protection"	...	IP40
Nominal voltage of surge suppressor	250 V / 50 Hz	...
Protection level of surge suppressor	≤ 1.3 kV (L/N)	...
Number of outlets	5 grounded outlets 10A/250V	...
Automatic delayed fuse	10 A / 250 V	...
Material	...	Plastic
Color	...	White
Nominal stroke current	2 kA (L/N) - 8/20 μs	...
Maximum stroke current	10 kA (L/N) - 8/20 μs 2 type	...
Response time	< 25 ns	...
Switch	two-way, with light indication	...
Manufacturer / Brand	...	Elektro-Plast Nasielsk
Main features	<ul style="list-style-type: none"> • Current paths shutters • DC filter to eliminate interferences : ≤ 35 dB 	<ul style="list-style-type: none"> • Claw or screw mounting • Cover fastened with latches • Flat housing profile : 22 mm
Housing	RACK 19", 1U, Plastic - non-flammable	...
Weight	0.93 kg	0.11 kg
Dimensions	484 x 54 x 55 mm	113 x 117 x 45 mm
Length of the cable	2.9 m	...
Guarantee	2 years	2 years