



	CELL HOLDER FOR 2 BATTERIES AKC-X2/18650	NVR NVR508-64B 64 CHANNELS UNIVIEW
		
	1.99 EUR 1.99 EUR	1166.47 EUR 1166.47 EUR
Standard	...	TCP/IP
Size	18650	...
Number of cells	2	...
Supported resolutions	...	max. 16 Mpx - 4608 x 3472 px
Connectors connection	serial	...
Current I	max. 1 A	...
Material	Plastic	...
Color	Black	...
Video outputs	...	1 pcs HDMI 4K 1 pcs VGA There is a possibility to configure a SPOT function on one of the output
Audio support	...	<ul style="list-style-type: none"> • 64 Channels - Audio from cameras • Bi-directional audio streaming support
Audio inputs	...	1 pcs CINCH
Audio outputs	...	1 pcs CINCH
Image compression method	...	Ultra 265 / H.265 / H.264
Bitrate	...	max. 320 Mbps
Supported hard drives	...	8 x 12 TB SATA
Recording modes	...	Manual, Sensor, Motion detection, Schedule
External storage devices backup	...	Backup to USB drive (pendrive, external drive)
Searching and playback the records	...	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) 1/4/6/8/9/16/25/36/64 channel synchronous playback
Network interface	...	2 x RJ-45 10/100/1000 Base-TX
Network functions	...	Full support via network, Remote records copying, Web-Server built-in max. 128 on-line users
Network protocols	...	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

ONVIF	...	✓
Default IP address	...	DHCP or 192.168.1.30
Default admin user / password	...	admin / 123456
Mobile phones support	...	Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EZView • iOS (iPhone): Free application EZView
Web browser access ports	...	80, 554
PC client access ports	...	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports	...	80
RTSP URL	...	rtsp://192.168.1.30:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.30:554/unicast/c1/s1/live - Sub stream
USB	...	2 x USB 2.0 1 x USB 3.0
Serial ports	...	RS-485
Alarm inputs / outputs	...	16 / 4
PTZ control	...	<ul style="list-style-type: none"> • PTZ Uniview cameras • RS-485 - PELCO-D/P and others
Motion Detection	...	✓
Intelligent image analysis	...	✓

Main features	...	<p>Functions implemented in cooperation between the recorder and cameras that support these functions</p> <ul style="list-style-type: none"> • Intelligent image analysis : crossing the line (tripwire), intrusion, entering the marked area, leaving the marked area, abandoned/missing object, scene changing, people counting, crowd gathering estimation, objects tracking • Smoke and temperature detection, fire detection • Audio detection • Motion detection with human/vehicle silhouette recognition • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • Fisheye-Dewarping - correction of the "fish eye" view to the perspective view • VIDEO signal loss alarm • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its
Mouse support	...	✓
IR remote controller in the set	...	—
Switch PoE	...	—
Power supply	...	100 ... 240 V AC
Power consumption	...	≤ 32 W (without HDD)
Operation temp	...	-10 °C ... 55 °C
Weight	0.014 kg	5 kg
Dimensions	<ul style="list-style-type: none"> • 76 x 40 x 20 mm • 14 cm - Length of the cables 	442 x 426 x 89 mm
Supported languages	...	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovak, Italian
Manufacturer / Brand	...	UNIVIEW
Guarantee	...	3 years