



	NVR NVR4108-8P-EI 8 CHANNELS, 8 PoE WizSense DAHUA	TV OR MONITOR MOUNT BS-106S
		
	458.41 EUR 458.41 EUR	8.24 EUR 8.24 EUR
Standard	TCP/IP	...
Mounting standard	...	VESA : 75, 100, 200, 400 x 200
Supported resolutions	max. 16 Mpx - 4608 x 3472 px	...
Screen size range	...	23 " ... 42 "
Bearing capacity	...	45 kg
Video outputs	1 pcs HDMI 4K 1 pcs VGA	...
Distance from mounting surface	...	19 mm from wall
Color	...	Black
Tilt adjustment	...	—
Audio support	<ul style="list-style-type: none"> • 8 Channels - Audio from cameras • Bi-directional audio streaming support 	...
Horizontal rotation	...	—
Audio inputs	1 pcs CINCH	...
Rotation in the plane of the screen	...	—
Audio outputs	1 pcs CINCH	...
Image compression method	Smart H.265+ / H.265 / Smart H.264+ / H.264 / MJPEG	...
Bitrate	max. 256 Mbps	...
Supported hard drives	1 x 16 TB SATA	...
Recording modes	Manual, Motion Detection, Schedule	...
External storage devices backup	Backup to USB drive (pendrive, external drive)	...
Searching and playback the records	<ul style="list-style-type: none"> • Records searching: by time and events type. Records playback: forward, backward, fast, slow • Advanced searching (to the one second accuracy) • Smart Playback function • Records playback from max. 8 channels in the same time @ 4 Mpx (without AI) • Records playback from max. 8 channels in the same time @ 1080p (AI) 	...
Network interface	1 x RJ-45 10/100/1000 Base-TX	...
Network functions	Full support via network, Remote records copying, Web-Server built-in	...
Network protocols	HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, SNMP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, IP Search, P2P, Auto Register	...
ONVIF	2.06	...
Default IP address	192.168.1.108	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Default admin user / password	admin / - The administrator password should be set at the first start	...
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS See how to configure the P2P function in Dahua recorders and how to enable the mobile application	...
Web browser access ports	80, 37777	...
PC client access ports	37777	...
Mobile client access ports	37777	...
RTSP URL	• rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream • rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...
USB	2 pcs USB 2.0	...
Serial ports	—	...
Alarm inputs / outputs	—	...
PTZ control	IP Speed Dome Cameras	...
Motion Detection	✓	...
Intelligent image analysis	✓	...
Main features	<ul style="list-style-type: none"> • Intelligent image analysis : crossing the line (tripwire), intrusion, scene changing, face detection • SMD PLUS - searching for an object classified as: human, motor vehicle • Filtering of false alarms based on the recognition of persons and vehicles • Quick Pick - AI technology enabling, together with the recorder, quick identification of interesting objects (people/vehicles) based on an artificial intelligence algorithm. It allows to extract and compare the colors of clothes and vehicles • Face recognition • Face analysis: determination of sex, age and characteristic elements of appearance (glasses, facial hair, mask) • Support for up to 10 face databases, including 20 000 face images • In the base other than face photography, can also be stored such information as: name, sex, date of birth, nationality, address, ID number • Intelligent face search by metadata of different targets or uploading pictures of faces to the device and comparing them with recorded faces by similarity • Privacy zones <p>Functions implemented in cooperation between the recorder and cameras that support these functions :</p> <ul style="list-style-type: none"> • ANPR • people counting • heat map 	...
Mouse support	✓	...
IR remote controller in the set	—	...



Switch PoE	8-port PoE Switch built-in, 25.5 W / Channel - PoE (802.3af/at)	...
Maximum total switch load	72 W	...
Power supply	53 V DC / 1.81 A (power adapter included)	...
Power consumption	max. 10 W (without HDD)	...
Operation temp	-10 °C ... 55 °C	...
Weight	0.69 kg	1.45 kg
Dimensions	270 x 206 x 48 mm	455 x 260 x 19 mm
Supported languages	Polish, English, Bulgarian, Czech, Finnish, Greek, Romanian, Serbian, Slovenian, Hungarian	...
Manufacturer / Brand	DAHUA	...
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00