


	SET OF UTP / COAXIAL CONVERTERS FOR LAN+POE TRANSMISSION XCOAX4-SET 2 PCS SET ATTE	ACCESS CONTROLLER WITH TEMPERATURE MEASUREMENT ASI7213X-T1 - 1080p DAHUA
		
	2816.82 CZK 2816.82 CZK	87927.93 CZK 87927.93 CZK
Sensor	...	1/2.8 " CMOS
Connectors	<ul style="list-style-type: none"> • 1 pcs RJ45 • 1 pcs cable terminal • 1 pcs BNC 	...
LAN ports	1 pcs RJ45 100 Mbps	...
Optical zoom	...	—
Matrix size	...	2.1 Mpx 120 x 90 px
View angle	...	50 °
Resolution	...	1920 x 1080 - 1080p 120 x 90 px
Standard	...	TCP/IP
Range of IR illumination	...	5 m
White light LED illuminator range	...	5 m
Temperature measurement	...	✓
Temperature measurement range	...	30 °C ... 50 °C
Accuracy of temperature measurement	...	± 0.1 °C
Face recognition distance	...	0.3 m ... 1.8 m (max 100 000 faces in the database)
RFID proximity reader built-in	...	13.56 MHz S50
Internal memory	...	Support storage of 300 000 records

LAN+PoE port configuration description	<ul style="list-style-type: none"> • xCOAX4-SW : PoE IN - Passive PoE ≤ 30 W, PoE (802.3at) ≤ 30 W, PoE (802.3af) ≤ 15 W ("+-": 1, 2 pins; "+/-": 3, 6 pins) or ("+-": 4, 5 pins; "+/-": 7, 8 pins) • xCOAX4-CAM : Port LAN 10/100Mb or LAN + PoE OUT - PoE (802.3bt) ≤ 60 W, PoE (802.3at) ≤ 30 W, PoE (802.3af) ≤ 15 W 	...
Video output	...	—
RS-485 interface	...	✓
RS-232 interface	...	✓
Wiegand interface	...	✓
USB	...	2 x USB 2.0
Memory card slot	...	—
Alarm inputs / outputs	...	2 / 2 - Relay outputs
Transmission range	<ul style="list-style-type: none"> < 1000 m @ Coaxial cable < 100 m @ xCOAX4-SW - Switch PoE < 100 m @ xCOAX4-CAM - IP Camera 	...
Audio	...	Speaker built-in
LED indicators	<ul style="list-style-type: none"> • PoE • LAN • Link • 10Mb 	...
Network interface	...	<ul style="list-style-type: none"> • 1 x 10/100 Base-T (RJ-45) • 1 x 10/100/1000 Base-T (RJ-45)
Protections	<ul style="list-style-type: none"> • Overvoltage - LAN, BNC • Short-circuit - xCOAX4-SW 	...
Network protocols	...	IPv4, RTSP, RTP, TCP, UDP, P2P
WEB Server	...	Built-in
Main features	<ul style="list-style-type: none"> • Plug & Play • Support for IP cameras and network devices • Full transparency for networks • Watchdog function - Coaxial cable 	...
ONVIF	...	✓
Default IP address	...	192.168.1.108

Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80, 37777
PC client access ports	...	37777
Operation temp	-25 °C ... 65 °C	...
Main features	...	<ul style="list-style-type: none"> • Temperature measurement • Built-in LCD display showing the image from the video camera and the result of temperature measurement - 7 " capacitive touch screen, 1024 x 600 px • Identification modes : PIN, Proximity identifier 13.56 MHz S50, Face recognition, Any combination of the above • Wiegand 34/26 • WDR - 120 dB - Wide Dynamic Range • LED indication • Buzzer for acoustic signaling of some system events • AGC - Automatic Gain Control • Sharpness - sharper image outlines • Day/Night mode (color/b&w/auto) • RESET button • AI detection : A solution dedicated to measuring temperature. The camera is able to detect increased object temperature
Power supply	xCOAX4-SW : <ul style="list-style-type: none"> • 10 ... 58 V DC - cable terminal • PoE 802.3af/at / PASSIVE • The output PoE voltage is equal to the input voltage 	12 V DC / 2 A (power adapter included)
Power consumption	1.35 W (total)	≤ 24 W
Housing	Plastic (PC)	Aluminum + Tempered glass
Color	...	Black + Silver
"Index of Protection"	IP20	—

Operation temp	...	<ul style="list-style-type: none"> • -10 °C ... 55 °C - without temperature measurement • 15 °C ... 32 °C - with temperature measurement
Weight	0.033 kg (single element)	2 kg
Dimensions	<ul style="list-style-type: none"> • 73 x 52 x 20 mm - xCOAX4-SW • 73 x 52 x 20 mm - xCOAX4-CAM 	313 x 130 x 59 mm
Montage hole diameter	...	37 mm
Supported languages	...	English
Manufacturer / Brand	ATTE	DAHUA
Guarantee	3 years	3 years

