



	<a href="#">IP CAMERA IPC-T42EP Wi-Fi TURRET SE - 4 Mpx 2.8 mm IMO</a>	<a href="#">CEE-CONNECTOR PCE-2256 400 V 32 A 5P 6H IP44 / IP54</a>
		
	38.60 EUR 38.60 EUR	7.66 EUR 7.66 EUR
Standard	IP	...
Rated voltage	...	400 V / 50 ... 60 Hz
Sensor	1/2.8 " Progressive Scan CMOS	...
Maximal current load	...	32 A
Number of poles	...	5P
Resolution	2560 x 1440 - 4 Mpx	...
Grounding	...	6h
Lens	2.8 mm	...
Electrical cable	...	max. 5 x 6 mm <sup>2</sup>
View angle	90 °	...
Cable terminals	...	screw terminals
Range of IR illumination	30 m	...
Plug type	...	CEE
Audio	<ul style="list-style-type: none"> <li>• Microphone built-in,</li> <li>• Audio transmission via network</li> </ul>	...
Contact material	...	CuZn
Image compression method	H.265	...
Maximum wire insulation diameter	...	22 mm
Main stream frame rate	25 fps @ 4 Mpx	...
ONVIF	✓	...
Color	...	Red
Network interface	<ul style="list-style-type: none"> <li>• Wi-Fi - IEEE 802.11 b/g/n</li> <li>• Ethernet ; 100 Mbps</li> </ul>	...
Mobile phones support	Access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">IMO</a></li> <li>• iOS (iPhone): Free application <a href="#">IMO</a></li> </ul>	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Default IP address	DHCP	...

Web browser access ports	—	...
PC client access ports	—	...
Mobile client access ports	—	...
WEB Server	—	...
RTSP URL	—	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...
Main features	Length of the cable : 0.4 m	...
Main features	<ul style="list-style-type: none"> <li>• Wi-Fi Module - IEEE 802.11 b/g/n, Range : 100 m (open area)</li> <li>• RESET button</li> <li>• D-ZOOM - Digital Zoom : 8x</li> <li>• Motion Detection - Remote configuration</li> <li>• Human detection</li> <li>• Alarm notifications - Sending instant motion-activated alerts to mobile phone</li> </ul>	...
Power supply	12 V DC / 0.5 A (power adapter included)	...
Power consumption	≤ 3 W	...
"Index of Protection"	—	IP44 / IP54
Weight	0.2 kg	0.28 kg
Dimensions	Ø 110 x 81 mm	168 x 99 x 73 mm
Supported languages	—	...
Manufacturer / Brand	DAHUA / IMOU	PCE
Guarantee	2 years	2 years